

Title (en)

DRIVE ARRANGEMENT FOR THE CORE OF A WINDING SPOOL FOR A TRANSFER STRIP OF A TRANSFER DISPENSER

Title (de)

GETRIEBEANORDNUNG ZUM ANTRIEB DES SPULENKERNS EINER AUFWICKELSPULE FÜR EIN TRANSFERBAND EINES TRANSFERDISPENSERS

Title (fr)

DISPOSITIF DE TRANSMISSION POUR L'ENTRAÎNEMENT DU NOYAU D'UNE BOBINE RECEPTRICE POUR BANDE DE TRANSFERT D'UN DISTRIBUTEUR DE TRANSFERT

Publication

**EP 0886621 B1 20000524 (DE)**

Application

**EP 97908161 A 19970303**

Priority

- DE 19609533 A 19960311
- EP 9701052 W 19970303

Abstract (en)

[origin: US6079660A] PCT No. PCT/EP97/01052 Sec. 371 Date Mar. 18, 1999 Sec. 102(e) Date Mar. 18, 1999 PCT Filed Mar. 3, 1997 PCT Pub. No. WO97/33824 PCT Pub. Date Sep. 18, 1997 In a gear arrangement for driving the spool core (11) of a take-up spool for a transfer tape (5) through the spool core (3) of a feed spool arranged laterally of and radially offset from the take-up spool in the housing (2) of a transfer dispenser or in a refill cassette (1) for a transfer dispenser, comprising a first gearwheel (28) which is driven by the feed spool and which meshes with a second gearwheel (26,27) designed to drive the take-up spool (11), the pitch diameter of the second gearwheel (27) being smaller than that of the first gearwheel (28), a slipping clutch (16) being provided between the spool core (11) of one of the two spools and the associated gearwheel (27) and a radially projecting annular disc (13;14) being disposed on each spool core (3;11) and its side facing the other spool, the two spool cores (3,11) bear partly against one another through their mutually opposite annular discs (13,14). In addition, the first gearwheel (28) is formed with inner teeth (28) which are integral with the spool core (3) of the feed spool and in the interior of which lies the second gearwheel (27), the take-up spool being mounted for rotation on a spindle (15) integral with the housing or the cassette through a central annular sleeve (25). The annular sleeve (25) has a lateral extension (26) which carries the second, externally toothed gearwheel (27) meshing with the first gearwheel (28).

IPC 1-7

**B65H 37/00**

IPC 8 full level

**B43L 19/00** (2006.01); **B65H 35/07** (2006.01); **B65H 37/00** (2006.01)

CPC (source: EP KR US)

**B65H 37/00** (2013.01 - KR); **B65H 37/007** (2013.01 - EP US); **Y10T 156/1795** (2015.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**US 6079660 A 20000627**; AT E193272 T1 20000615; BR 9708020 A 19990727; CA 2248776 A1 19970918; CN 1071282 C 20010919; CN 1211959 A 19990324; DE 19609533 C1 19970227; DE 59701760 D1 20000629; DK 0886621 T3 20001009; EP 0886621 A1 19981230; EP 0886621 B1 20000524; ES 2146462 T3 20000801; GR 3033673 T3 20001031; JP 2000506109 A 20000523; KR 100458175 B1 20060127; KR 19990087677 A 19991227; NO 311250 B1 20011105; NO 984122 D0 19980907; NO 984122 L 19981109; PL 182980 B1 20020531; PL 328604 A1 19990201; PT 886621 E 20001031; RU 2181337 C2 20020420; TR 199801796 T2 19981221; TW 370510 B 19990921; WO 9733824 A1 19970918; ZA 972057 B 19970911

DOCDB simple family (application)

**US 14267499 A 19990318**; AT 97908161 T 19970303; BR 9708020 A 19970303; CA 2248776 A 19970303; CN 97192562 A 19970303; DE 19609533 A 19960311; DE 59701760 T 19970303; DK 97908161 T 19970303; EP 9701052 W 19970303; EP 97908161 A 19970303; ES 97908161 T 19970303; GR 20000401360 T 20000614; JP 53224297 A 19970303; KR 19980707142 A 19980910; NO 984122 A 19980907; PL 32860497 A 19970303; PT 97908161 T 19970303; RU 98118682 A 19970303; TR 9801796 T 19970303; TW 86101394 A 19970205; ZA 972057 A 19970310