

Title (en)
THREAD-DELIVERY APPARATUS

Title (de)
FADENLIEFERGERÄT

Title (fr)
SYSTEME D'ALIMENTATION EN FIL

Publication
EP 0886688 B1 20000621 (DE)

Application
EP 97915362 A 19970312

Priority
• DE 19609871 A 19960313
• EP 9701277 W 19970312

Abstract (en)
[origin: DE19609871A1] The invention concerns a thread-delivery apparatus (F) with a storage drum (1), a housing boom (6) which is rigid with the housing, and a controlled thread-draw-off brake (B) which is mounted in the housing boom (6) in an axially adjustable manner and comprises an annular brake body (8) which cooperates with a thread-draw-off region (4) of the storage drum (1) and has an outer support ring (9). The outer support ring (9) can be displaced in an annular mounting (7) of the boom (6) within an axial clearance (S) predetermined by axial counter stops (20, 21) and comprises at least one pair of sliding drives (10, 11) which act in opposite senses on the support ring (9) and are disposed on the mounting (7). According to the invention, disposed on at least one axial lateral surface (31, 32) of the support ring (9) is at least one group (2, 2') comprising a plurality of lift-adjusting ramps (2a, 2b, 2c) of different heights which can each be aligned alternatively on an axial counter stop (20, 21) facing this lateral surface.

IPC 1-7
D03D 47/34; **B65H 51/22**

IPC 8 full level
B65H 51/22 (2006.01); **D03D 47/34** (2006.01); **D03D 47/36** (2006.01)

CPC (source: EP US)
D03D 47/364 (2013.01 - EP US); **D03D 47/365** (2013.01 - EP US); **D03D 47/366** (2013.01 - EP US); **B65H 2551/20** (2013.01 - EP US)

Designated contracting state (EPC)
DE IT SE

DOCDB simple family (publication)
DE 19609871 A1 19970918; DE 59701913 D1 20000727; EP 0886688 A1 19981230; EP 0886688 B1 20000621; US 6095199 A 20000801; WO 9734035 A1 19970918

DOCDB simple family (application)
DE 19609871 A 19960313; DE 59701913 T 19970312; EP 9701277 W 19970312; EP 97915362 A 19970312; US 14244199 A 19990429