

Title (en)
Printer apparatus

Title (de)
Druckvorrichtung

Title (fr)
Appareil d'impression

Publication
EP 0894640 A3 19990728 (EN)

Application
EP 98306098 A 19980730

Priority
JP 20506597 A 19970730

Abstract (en)
[origin: EP0894640A2] A printer apparatus which improves operability during maintenance such as releasing paper jams or head cleaning and which has a reduced number of parts. The printer apparatus (10) has a cam mechanism (141-143) which operates with opening of the cover member (130) to release the biasing force normally acting on the head block (180) and at the same time moving the head block out of contact with the platen (193). <IMAGE>

IPC 1-7
B41J 29/38

IPC 8 full level
B41J 29/13 (2006.01); **B41J 2/32** (2006.01); **B41J 25/304** (2006.01); **B41J 25/312** (2006.01); **B41J 25/316** (2006.01)

CPC (source: EP)
B41J 25/304 (2013.01); **B41J 25/316** (2013.01)

Citation (search report)

- [XY] EP 0324129 A2 19890719 - TOKYO ELECTRIC CO LTD [JP]
- [PXA] EP 0806297 A2 19971112 - FUJITSU TAKAMISAWA COMPONENT [JP]
- [DY] US 5599113 A 19970204 - SUZUKI MINORU [JP], et al
- [A] JP S648055 A 19890112 - TOKYO ELECTRIC CO LTD
- [A] EP 0515234 A1 19921125 - SUMMIT WORLD TRADE CORP [US]
- [X] PATENT ABSTRACTS OF JAPAN vol. 016, no. 467 (M - 1317) 29 September 1992 (1992-09-29)
- [A] PATENT ABSTRACTS OF JAPAN vol. 012, no. 014 (M - 659) 16 January 1988 (1988-01-16)

Cited by
EP1052107A3; EP1323535A3; RU2481958C2; EP1698476A1; US7503714B2; JP2012076248A

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 0894640 A2 19990203; EP 0894640 A3 19990728; CA 2241401 A1 19990130; CN 1210789 A 19990317; JP H1148507 A 19990223; KR 19990014280 A 19990225; SG 74066 A1 20000718

DOCDB simple family (application)
EP 98306098 A 19980730; CA 2241401 A 19980729; CN 98117874 A 19980730; JP 20506597 A 19970730; KR 19980030717 A 19980729; SG 1998002689 A 19980727