

Title (en)

Heat-resistant zinc alloy and molded article thereof

Title (de)

Hitzebeständige Zinklegierung und daraus geformter Gegenstand

Title (fr)

Alliage de zinc thermorésistant et article moulé en celui-ci

Publication

**EP 0899349 A1 19990303 (EN)**

Application

**EP 98115159 A 19980812**

Priority

JP 21839397 A 19970813

Abstract (en)

A heat-resistant zinc alloy exhibiting good creep resistance even at a temperature of not less than 100 DEG C comprises at least one of nickel and manganese in a total amount of not more than 3.5% by weight based on the total weight of the alloy, titanium and/or zirconium by not more than 2%wt, optionally aluminium by not more than 0.5%wt, copper by not more than 2%wt as well as one or more of Cr, Sc, Be, Li, Y and lanthanoids by not more than 0.5%wt in total and the balance of zinc and inevitable impurities. A molded article comprises the heat-resistant zinc alloy defined above. The heat-resistant zinc alloy is excellent in the creep resistance even at a high temperature and thus the heat-resistant zinc alloy can considerably expand the fields of application of the molded articles produced from the alloy.

IPC 1-7

**C22C 18/00**

IPC 8 full level

**C22C 18/00** (2006.01)

CPC (source: EP)

**C22C 18/00** (2013.01)

Citation (search report)

- [X] FR 2083866 A5 19711217 - METALLGESELLSCHAFT AG
- [X] GB 2066853 A 19810715 - CENTRE RECH METALLURGIQUE
- [X] BE 775207 A 19720510 - CENTRE RECH METALLURGIQUE
- [A] FR 2366370 A1 19780428 - CENTRE RECH METALLURGIQUE [BE]
- [X] PATENT ABSTRACTS OF JAPAN vol. 097, no. 006 30 June 1997 (1997-06-30)

Cited by

WO2015031509A1; CN108165797A; US2016168664A1; EP3039165A4; CN115874084A; WO2015192279A1; US10926312B2

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 0899349 A1 19990303**; JP H1161299 A 19990305

DOCDB simple family (application)

**EP 98115159 A 19980812**; JP 21839397 A 19970813