

Title (en)

Hyper-eutectic al-si alloy coating respectively an al-si composite

Title (de)

Beschichtung aus einer übereutektischen Aluminium/Silizium Legierung bzw. einem Aluminium/Silizium Verbundwerkstoff

Title (fr)

Revêtement d'un alliage al-si hyper-eutectique respectivement un al-si composite

Publication

EP 0899354 A1 19990303 (DE)

Application

EP 98113379 A 19980717

Priority

DE 19733204 A 19970801

Abstract (en)

A hypereutectic aluminium-silicon alloy or aluminium-silicon composite material coating has a heterogeneous structure of an aluminium solid solution, intermetallic phases such as Mg₂Si, oxides and (i) silicon precipitates, (ii) embedded silicon particles or (iii) silicon precipitates and embedded silicon particles, the mean size of the primary silicon precipitates or embedded silicon particles being less than 10 μm, the mean oxide size being less than 5 μm and the coating being mainly copper-free, i.e. the copper content is less than 1 (preferably less than 0.1, especially less than 0.01) wt%. Also claimed are processes for producing the above coatings by thermal (especially atmospheric plasma) spraying with parameters adjusted for formation of oxides. Preferably, the spraying material has the composition (by wt.) (A) (for coating type (i)) 23-40 (especially 25%) Si, 0.8-2.0 (especially 1.2%) Mg, NOTGREATER 0.6% Zr, NOTGREATER 0.25% Fe, NOTGREATER 0.01% each of Mn, Ni, Cu and Zn and balance Al; (B) (for coating type (i)) as (A) but containing 23-40 (especially 25%) Si, 1-5 (especially 4%) Ni and 1.0-1.4 (especially 1.2%) Fe; (C) (for coating type (ii)) 5-50% Si particles and 50-95% alloy particles of composition (A) but containing 0-11.8 (especially 9%) Si; (D) (for coating type (ii)) 5-50% Si particles and 50-95% alloy particles of composition (B) but containing 0-11.8 (especially 9%) Si; (E) (for coating type (iii)) 5-50% Si particles and 50-95% alloy particles of composition (A) but containing 11.8-40 (especially 17%) Si; or (F) (for coating type (iii)) 5-50% Si particles and 50-95% alloy particles of composition (B) but containing 11.8-40 (especially 17%) Si.

Abstract (de)

Die Erfindung betrifft eine tribologische Beschichtung aus einer kupfer-freien, stark übereutektischen, Aluminium/Silizium-Legierung bzw. aus einem kupfer-freien, Aluminium/Silizium-Verbundwerkstoff, die so zusammengesetzt sind, daß feine Silizium-Primärkristalle bzw. Silizium-Partikel, intermetallische Phasen und Oxide als harte Partikel bei der Herstellung der Schichten im atmosphärischen, thermischen Spritzverfahren sich bilden bzw. in der Gefügestruktur verankert werden. Aufgrund der intermetallischen Phasen wie Mg₂Si und der Oxide lässt sich die Oberfläche der Beschichtung wirtschaftlich mit konventionellen Werkzeugen kurzspanend bearbeiten, so daß auf weitere Legierungselemente wie Kupfer zur Bildung von weiteren intermetallischen Phasen wie Al₂Cu verzichtet werden kann. Dies hat eine besondere Bedeutung beim Einsatz dieser Schichten als Zylinderlaufbahn in einer Hubkolbenmaschine, denn herkömmliche AlSi-Laufbahnen bereiten aufgrund ihres Kupferanteiles Probleme in Verbindung mit bestimmten Kraftstoffen. <IMAGE>

IPC 1-7

C23C 4/04; C23C 4/12

IPC 8 full level

F02F 1/00 (2006.01); **B22F 1/148** (2022.01); **C22C 21/02** (2006.01); **C23C 4/04** (2006.01); **C23C 4/06** (2016.01); **C23C 4/12** (2006.01); **C23C 4/134** (2016.01); **C23C 30/00** (2006.01); **F02F 7/00** (2006.01); **F16J 10/04** (2006.01)

CPC (source: EP KR US)

B22F 1/148 (2022.01 - EP KR US); **C22C 1/0416** (2013.01 - EP); **C22C 21/02** (2013.01 - EP US); **C23C 4/06** (2013.01 - EP US); **C23C 4/134** (2016.01 - EP US); **C23C 28/00** (2013.01 - KR); **C23C 30/00** (2013.01 - EP US); **F02F 7/0085** (2013.01 - EP US); **Y10T 428/12097** (2015.01 - EP US); **Y10T 428/12104** (2015.01 - EP US); **Y10T 428/12139** (2015.01 - EP US); **Y10T 428/12736** (2015.01 - EP US); **Y10T 428/12757** (2015.01 - EP US)

Citation (search report)

- [A] US 4707379 A 19871117 - NEUFUSS KAREL [CS], et al
- [A] WO 9713884 A1 19970417 - FORD MOTOR CO [GB], et al
- [A] PATENT ABSTRACTS OF JAPAN vol. 006, no. 054 (C - 097) 9 April 1982 (1982-04-09)
- [A] PATENT ABSTRACTS OF JAPAN vol. 009, no. 088 (C - 276) 17 April 1985 (1985-04-17)
- [A] PATENT ABSTRACTS OF JAPAN vol. 095, no. 002 31 March 1995 (1995-03-31)
- [A] PATENT ABSTRACTS OF JAPAN vol. 007, no. 155 (C - 175) 7 July 1983 (1983-07-07)
- [A] PATENT ABSTRACTS OF JAPAN vol. 018, no. 108 (M - 1564) 22 February 1994 (1994-02-22)

Cited by

EP1036857A1; EP1148229A3; EP1176228A3; EP0987339A1; US6257018B1; US6329021B1

Designated contracting state (EPC)

DE ES FR GB IT SE

DOCDB simple family (publication)

DE 19733204 A1 19990204; DE 19733204 B4 20050609; DE 59809547 D1 20031016; EP 0899354 A1 19990303; EP 0899354 B1 20030910; JP 3049605 B2 20000605; JP H11152557 A 19990608; KR 100304479 B1 20011122; KR 19990023259 A 19990325; US 6221504 B1 20010424

DOCDB simple family (application)

DE 19733204 A 19970801; DE 59809547 T 19980717; EP 98113379 A 19980717; JP 24901198 A 19980731; KR 19980030989 A 19980731; US 12779498 A 19980803