

Title (en)

Device for applying damping solution onto a cylinder of a rotary printing press

Title (de)

Vorrichtung zum Auftragen von Feuchtmittel auf einen Zylinder einer Rotationsdruckmaschine

Title (fr)

Dispositif pour appliquer du liquide de mouillage sur un cylindre d'une presse rotative

Publication

**EP 0901903 A3 19991027 (DE)**

Application

**EP 98117241 A 19980911**

Priority

DE 19740476 A 19970915

Abstract (en)

[origin: EP0901903A2] Nozzles (6) are positioned along the length of the cylinders (2,5) of the machine, producing jets which are deflected and atomized by plates (9), nozzles and plates being located in a housing (13) which is open to the cylinder. At least one adjusting member is provided to maximum metering of moisturizing medium on the delivery side. Preferably the angle of the deflector plates can be adjusted by pivoting.

IPC 1-7

**B41F 7/30**

IPC 8 full level

**B41F 7/30** (2006.01)

CPC (source: EP US)

**B41F 7/30** (2013.01 - EP US)

Citation (search report)

- [XY] DE 2462162 A1 19760325 - MASCHF AUGSBURG NUERNBERG AG
- [YD] DE 571854 C 19330306 - ARTUR BANNIZA, et al
- [Y] US 5622110 A 19970422 - ORZECHOWSKI THOMAS W [US], et al
- [Y] EP 0525556 A1 19930203 - KOENIG & BAUER AG [DE]
- [Y] DE 872050 C 19530330 - MAX RAS DR
- [A] US 3992992 A 19761123 - SMITH WALTER S
- [A] US 5595116 A 19970121 - OHKAWARA TAMAKI [JP]
- [A] EP 0621132 A1 19941026 - JIMEK INT AB [SE]

Cited by

US9067403B2; WO2009155898A3

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 0901903 A2 19990317; EP 0901903 A3 19991027;** DE 19838020 A1 19990318; US 6089153 A 20000718

DOCDB simple family (application)

**EP 98117241 A 19980911;** DE 19838020 A 19980821; US 15371098 A 19980915