

Publication

EP 0902130 A3 19990428 (FR)

Application

EP 98116729 A 19980903

Priority

DE 19740489 A 19970915

Abstract (en)

[origin: EP0902130A2] Base frame (2) having shape corresponding to that of the manhole frame has a cutting ring (12) with cutting edge (13) underneath, which can be raised by an arrangement of a lifting beams (6) and hydraulic cylinder (5). Flexible connecting links (11) are provided on a lifting device (7) with several horizontal expanding arms (8). The cylinder and the expanding arms are supplied by a central hydraulic unit (19) and valves (20, 21) allow them to be shut off individually.

IPC 1-7

E02D 29/14

IPC 8 full level

E02D 29/14 (2006.01)

CPC (source: EP)

E02D 29/1445 (2013.01)

Citation (search report)

- [A] DE 29608097 U1 19960613 - JOCH HANS [DE]
- [A] DE 19542771 A1 19960704 - VESTER KNUD ERIK [DK]

Cited by

ITVI20080285A1; DE19912188A1; CN114801966A; CN116873837A

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0902130 A2 19990317; EP 0902130 A3 19990428; DE 19740489 A1 19990325; DE 19740489 C2 19990715

DOCDB simple family (application)

EP 98116729 A 19980903; DE 19740489 A 19970915