

Title (en)

Lock cylinder and key for such a lock cylinder

Title (de)

Zylinderschloss und Schlüssel dafür

Title (fr)

Cylindre de serrure et clé pour un tel cylindre

Publication

**EP 0902138 B1 20040211 (FR)**

Application

**EP 98402057 A 19980813**

Priority

FR 9711403 A 19970912

Abstract (en)

[origin: EP0902138A1] The lock is operated by a rotary bit (13) which is engaged with an outer rotor (2) and disengaged by an inner one (3) when a key (10) is inserted by means of connectors (18,20,24,25). The lock comprises a stator (1) with an outer rotor mounted inside it, an inner rotor and a rotary bit which engages with or disengages from the rotors. The bit is engaged with the inner rotor and disengaged from the outer one in the absence of a key. It engages with the outer rotor and disengages from the inner one when a key is inserted by means of coded connectors (18,20,24,25). At least one of the connectors is in the form of an axial pin (24) with a return spring (28), actuated by a pusher (18) and lateral pin (20).

IPC 1-7

**E05B 9/10; E05B 27/04; E05B 27/10**

IPC 8 full level

**E05B 9/10** (2006.01); **E05B 27/04** (2006.01); **E05B 17/04** (2006.01); **E05B 27/00** (2006.01); **E05B 63/00** (2006.01)

CPC (source: EP)

**E05B 9/10** (2013.01); **E05B 27/0032** (2013.01); **E05B 63/0078** (2013.01)

Cited by

EP2644809A1; FR2803323A1; DE102007000203A1; FR2988760A1; WO0149960A1

Designated contracting state (EPC)

BE FR GB LU NL

DOCDB simple family (publication)

**EP 0902138 A1 19990317; EP 0902138 B1 20040211; FR 2768454 A1 19990319; FR 2768454 B1 19991203**

DOCDB simple family (application)

**EP 98402057 A 19980813; FR 9711403 A 19970912**