

Publication

EP 0903312 A3 19990428

Application

EP 98117041 A 19980909

Priority

DE 19741618 A 19970920

Abstract (en)

[origin: EP0903312A2] The cutter device (1) has a support surface (2) for the adhesive tape (22) to be cut, with two side rails (3) to guide the tape along its edges. A cutter knife (4) is positioned on the inner side of one or both side rails so that the cutter blades slope at an angle to the support surface. The angle is between 85 degrees and 2 degrees , pref. 50 degrees to 5 degrees . The cutter knives are positioned on the side where a cut piece of tape is removed.

IPC 1-7

B65H 35/00

IPC 8 full level

B65H 35/00 (2006.01)

CPC (source: EP US)

B65H 35/0026 (2013.01 - EP US); **B65H 35/008** (2013.01 - EP US); **Y10T 83/6644** (2015.04 - EP US); **Y10T 83/739** (2015.04 - EP US); **Y10T 83/8818** (2015.04 - EP US); **Y10T 83/896** (2015.04 - EP US); **Y10T 156/1788** (2015.01 - EP US); **Y10T 156/1795** (2015.01 - EP US); **Y10T 225/206** (2015.04 - EP US); **Y10T 225/209** (2015.04 - EP US); **Y10T 225/21** (2015.04 - EP US); **Y10T 225/211** (2015.04 - EP US)

Citation (search report)

- [XA] DE 1083153 B 19600609 - CLAUS KOENIG G M B H
- [X] US 3635473 A 19720118 - SASAKI OSAMU, et al
- [XA] DE 1085440 B 19600714 - CLAUS KOENIG G M B H
- [X] DE 2161337 A1 19720713
- [A] DE 8904789 U1 19890810
- [A] GB 765497 A 19570109 - JOHNSON & JOHNSON

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0903312 A2 19990324; **EP 0903312 A3 19990428**; **EP 0903312 B1 20040414**; DE 19741618 A1 19990401; DE 59811180 D1 20040519; ES 2217472 T3 20041101; US 6553884 B1 20030429

DOCDB simple family (application)

EP 98117041 A 19980909; DE 19741618 A 19970920; DE 59811180 T 19980909; ES 98117041 T 19980909; US 15412398 A 19980916