

Title (en)

Spinning method and machine with condenser

Title (de)

Spinnverfahren und Spinnmaschine mit Kondensiervorrichtung

Title (fr)

Procédé et machine de filature avec condenseur

Publication

EP 0903430 A3 20000510 (DE)

Application

EP 98810857 A 19980831

Priority

CH 224197 A 19970923

Abstract (en)

[origin: EP0903430A2] A ring spinning drafting system (1) is followed by a perforated condensing roller (10) equipped with internal suction. A nip roller (13) acts a twist-stop for the twist traveling back from the spindle (3). The yarn (2) leaves at the nip line (K) so that it is not deflected any further by the condensing roller (10). The angle (F) between the yarn (2) and the line (N) joining the centers of the rollers (10,13) is greater or equal to 90 degrees . An Independent claim is also included for a spinning process, especially using a ring spindle as the twisting device, where the sliver is twisted without being supported by the condensing surface but only by the twist stop (13).

IPC 1-7

D01H 5/72

IPC 8 full level

D01H 1/02 (2006.01); **D01H 5/72** (2006.01); **D01H 5/74** (2006.01)

CPC (source: EP)

D01H 5/72 (2013.01)

Citation (search report)

- [XA] DE 19500036 A1 19960704 - RIETER AG MASCHF [CH]
- [XA] FR 2627194 A1 19890818 - FEHRER ERNST [AT]
- [A] FR 2583784 A1 19861226 - ASA SA [FR]

Cited by

EP1054087A1; JP2009509061A; JP2002069762A; CN109811442A; DE102019116457A1; CN103789881A; CN107177910A; EP1110855A2; WO2009060298A3

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0903430 A2 19990324; EP 0903430 A3 20000510; EP 0903430 B1 20030409; AT E237012 T1 20030415; DE 59807821 D1 20030515

DOCDB simple family (application)

EP 98810857 A 19980831; AT 98810857 T 19980831; DE 59807821 T 19980831