

Title (en)

Process for reducing the adhesion between a wet fibrous web and a rotating roller

Title (de)

Verfahren zur Verringerung der Haftung einer feuchten Faserstoffbahn an einer rotierenden Walze

Title (fr)

Procédé pour diminuer l'adhésion entre une bande fibreuse humide et un rouleau rotatif

Publication

EP 0903437 A3 20000405 (DE)

Application

EP 98112932 A 19980711

Priority

DE 19741517 A 19970920

Abstract (en)

[origin: EP0903437A2] A steam cushion is formed between a fiber web (1) and a rotating roller (4). The roller (4) is heated to temperature higher than that required to dry the web (1) or for extracting water from it, giving a roller surface temp. of ≥ 120 degrees C. Steam is blown into the entry gap between the roller (4) and the web (1), the web (1) temp. being ≤ 70 degrees C and having a dry matter content of ≤ 60 %.

IPC 1-7

D21F 3/02; **D21F 5/02**; **D21F 5/04**

IPC 8 full level

D21F 3/02 (2006.01); **D21F 5/02** (2006.01); **F26B 13/04** (2006.01)

CPC (source: EP US)

D21F 3/02 (2013.01 - EP US); **D21F 3/0272** (2013.01 - EP US); **D21F 5/02** (2013.01 - EP US)

Citation (search report)

- [X] US 5404653 A 19950411 - SKAUGEN BORGEIR [US], et al
- [X] US 3798785 A 19740326 - CHAMOUTON D
- [X] GB 598111 A 19480211 - CARRIER ROSS ENGINEERING COMPA, et al
- [X] WO 9001085 A1 19900208 - BELOIT CORP [US]
- [X] DE 579525 C 19330627 - NETZSCHKAUER MASCHINENFABRIK F
- [X] DE 588546 C 19331125 - RUDOLF STEINMETZ
- [A] US 3097933 A 19630716 - KELLOGG HARRY B, et al
- [A] EP 0620313 A2 19941019 - VALMET PAPER MACHINERY INC [FI]

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0903437 A2 19990324; **EP 0903437 A3 20000405**; DE 19741517 A1 19990325; US 2001007279 A1 20010712; US 6436239 B2 20020820

DOCDB simple family (application)

EP 98112932 A 19980711; DE 19741517 A 19970920; US 15334498 A 19980915