

Title (en)  
Battery Holder

Title (de)  
Batteriehalter

Title (fr)  
Support de batterie

Publication  
**EP 0905803 B1 20030226 (EN)**

Application  
**EP 98118495 A 19980930**

Priority  
JP 26523797 A 19970930

Abstract (en)  
[origin: EP0905803A1] An object of the invention is to provide a battery holder which allows a number of battery holders to be arranged under a state where both the ends of batteries (1) are supported by the support members (2) and the support members (2) are laterally arranged, which is advantageous in view of a space, and in which heat generated from sealed-type batteries (1) can be rapidly dissipated to the exterior. In order to attain the object, a battery holder consists of one plate-like support member (2) and another support member (2'). A plurality of battery holes (2a) of a predetermined depth into which sealed portions of a positive or negative side of sealed-type batteries (1) that are clamped at one side by the support member (2) are to be respectively fitted are formed in one face of the support member (2), so that one row of the battery holes (2a) is a row for positive electrodes and another row of the battery holes (2a) is a row for negative electrodes. An electrode hole (2b) is formed in a bottom face of each of the battery holes (2a). A groove (2c) is formed between adjacent paired positive-electrode and negative-electrode holes among the electrode holes (2b) disposed in the bottom faces of the electrode holes (2b) of the rows. The paired positive-electrode and negative-electrode holes are communicated with each other through the groove (2c). Vent holes (2d) are opened at appropriate places among the battery holes (2a). In each of the one and other rows of the other support member (2'), only the battery hole (2a) for a positive electrode or a negative electrode is formed at each of opposite end portions. <IMAGE>

IPC 1-7  
**H01M 2/10**; **H01M 6/44**; **H01M 2/20**

IPC 8 full level  
**H01M 6/44** (2006.01); **H01M 50/51** (2021.01); **H01M 50/517** (2021.01); **H01M 50/588** (2021.01)

CPC (source: EP US)  
**H01M 6/44** (2013.01 - EP US); **H01M 10/613** (2015.04 - EP US); **H01M 10/643** (2015.04 - EP US); **H01M 10/6562** (2015.04 - EP US); **H01M 10/6566** (2015.04 - EP US); **H01M 50/213** (2021.01 - EP US); **H01M 50/51** (2021.01 - EP US); **H01M 50/517** (2021.01 - EP US); **H01M 10/6556** (2015.04 - EP US); **H01M 10/6563** (2015.04 - EP US); **H01M 50/588** (2021.01 - EP US); **Y02E 60/10** (2013.01 - EP)

Cited by  
FR3098999A1; WO2021009467A1; EP1091429A1; EP1109237A1; EP2698839A4; DE102015122844A1; FR2963485A1; CN103038916A; EP1069631A1; CN102623651A; EP1872418A4; EP2154740A3; EP2157634A3; EP1880433A4; US6399238B1; US6400122B1; US10175037B2; WO2012013641A1; US6627345B1; US8420249B2; WO2006124663A2; US9065103B2; TWI493772B; TWI484684B; US7483636B2

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**EP 0905803 A1 19990331**; **EP 0905803 B1 20030226**; CN 1213189 A 19990407; DE 69811589 D1 20030403; DE 69811589 T2 20030925; JP 3777748 B2 20060524; JP H11111248 A 19990423; US 6174618 B1 20010116

DOCDB simple family (application)  
**EP 98118495 A 19980930**; CN 98119401 A 19980930; DE 69811589 T 19980930; JP 26523797 A 19970930; US 16300398 A 19980930