

Title (en)
Light perforated brick

Title (de)
Leicht-Hochlochziegel

Title (fr)
Brique perforée légère

Publication
EP 0909857 B1 20010103 (DE)

Application
EP 97117919 A 19971016

Priority
EP 97117919 A 19971016

Abstract (en)
[origin: EP0909857A1] Holes (6,7) form channels through the brick, between which are connecting webs (8) The ratio between the width of the webs measured in the direction of the outside walls (2,3) and the width of the channels, measured in the same direction, is 1:1.3 to 1:1.8. Width of the webs is preferably 3.5 - 4.1 mm and the channels take up 55-60% of the brick cross section.

IPC 1-7
E04B 2/14

IPC 8 full level
E04B 2/14 (2006.01); **E04B 2/02** (2006.01)

CPC (source: EP)
E04B 2/14 (2013.01); **E04B 2002/0208** (2013.01)

Cited by
EP3904617A1; EP1662061A1; DE202004021740U1

Designated contracting state (EPC)
AT BE CH DE ES FR IT LI NL

DOCDB simple family (publication)
EP 0909857 A1 19990421; **EP 0909857 B1 20010103**; AT E198496 T1 20010115; DE 59702860 D1 20010208; ES 2154010 T3 20010316

DOCDB simple family (application)
EP 97117919 A 19971016; AT 97117919 T 19971016; DE 59702860 T 19971016; ES 97117919 T 19971016