

Title (en)
MULTI-FUNCTION LIGHT SENSOR FOR VEHICLE

Title (de)
MULTIFUNKTION-LICHTSENSOR FÜR FAHRZEUG

Title (fr)
CAPTEUR DE LUMIERE A FONCTIONS MULTIPLES POUR VEHICULE

Publication
EP 0910525 B1 20010704 (EN)

Application
EP 98921198 A 19980513

Priority
• US 9809841 W 19980513
• US 85613897 A 19970514

Abstract (en)
[origin: WO9851549A1] A system for detecting the presence of rain droplets on a windshield employs a source of radiant energy, such as an LED (70), and a photodetector installed on the instrument panel of a vehicle. The LED (70) and the photodiode (85) are arranged with respect to one another such that light from the LED (70) cannot reflect directly off the windshield (81) onto the photodiode (85). Only when the light from the LED is back scattered by an environmental condition, such as the raindrops on the exterior (82) of the windshield, the condensation of moisture on the interior (80) of the windshield, or the presence of smoke in the cabin, will the photodiode receive the light from the LED. Each of these environmental conditions has a predeterminable characteristic signature that permits the processing of data to detect same. An ambient light signal is subtracted from the combination of the rain and ambient light signals by pulsed operation of the LED and subtracting the ambient light signal, which is detected when the LED is dark, from the combined LED and ambient light signal which is present when the LED is illuminated. A further LED (100) is provided to effect a fog detection system that detects condensation on the interior of the vehicle windshield. The further LED (100) illuminates the photodiode in a manner whereby the light on the photodiode is reduced when condensation is present. Also, a monitoring arrangement that employs a separate light sensor provides compensation for variances resulting from component aging and thermal influences.

IPC 1-7
B60S 1/08

IPC 8 full level
B60S 1/08 (2006.01)

CPC (source: EP US)
B60S 1/0818 (2013.01 - EP US); **B60S 1/0822** (2013.01 - EP US); **B60S 1/0833** (2013.01 - EP US); **B60S 1/0888** (2013.01 - EP US); **Y10S 15/15** (2013.01 - US); **Y10S 318/02** (2013.01 - EP US)

Cited by
DE102007045259A1; DE102006039034A1

Designated contracting state (EPC)
DE FR IT SE

DOCDB simple family (publication)
WO 9851549 A1 19981119; DE 69801033 D1 20010809; DE 69801033 T2 20020321; EP 0910525 A1 19990428; EP 0910525 B1 20010704; US 6118383 A 20000912

DOCDB simple family (application)
US 9809841 W 19980513; DE 69801033 T 19980513; EP 98921198 A 19980513; US 85613897 A 19970514