

Title (en)
Continuous casting mould

Title (de)
Stranggiesskokille

Title (fr)
Lingotière de coulée continue

Publication
EP 0914888 B1 20040825 (DE)

Application
EP 98120153 A 19981027

Priority
DE 19748305 A 19971031

Abstract (en)
[origin: US6142212A] A continuous casting mold with two oppositely located short side walls and two oppositely located long side walls which extend past the short side walls, wherein at least one of the short side walls is moveable by an adjusting member toward or away from the other short side wall. The adjusting member is constructed in the form of two hydraulic cylinder units which can be actuated independently from each other, wherein each hydraulic cylinder unit has a cylinder and a piston which is adjustable relative to the cylinder in an adjusting direction.

IPC 1-7
B22D 11/04; **B22D 11/16**

IPC 8 full level
B22D 11/04 (2006.01); **B22D 11/05** (2006.01); **B22D 11/16** (2006.01)

CPC (source: EP US)
B22D 11/05 (2013.01 - EP US); **B22D 11/168** (2013.01 - EP US)

Cited by
EP1486273A1; CN102601328A; AT519154A1; AT519154B1; EP3623075A3; DE102007039882A1; WO2018055038A1; WO2006042603A1

Designated contracting state (EPC)
AT BE DE ES FI FR GB IT LU NL SE

DOCDB simple family (publication)
US 6142212 A 20001107; AT E274387 T1 20040915; CN 1083306 C 20020424; CN 1219448 A 19990616; DE 19748305 A1 19990506; DE 59811862 D1 20040930; EP 0914888 A1 19990512; EP 0914888 B1 20040825; ES 2226052 T3 20050316; JP 4745473 B2 20110810; JP H11207443 A 19990803

DOCDB simple family (application)
US 17729698 A 19981022; AT 98120153 T 19981027; CN 98124569 A 19981031; DE 19748305 A 19971031; DE 59811862 T 19981027; EP 98120153 A 19981027; ES 98120153 T 19981027; JP 30736098 A 19981028