

Title (en)

Pneumatic tyre for passenger cars and method of manufacture thereof

Title (de)

PKW-Reifen und Verfahren zu seiner Herstellung

Title (fr)

Bandage pneumatique pour véhicules de tourisme et son procédé de fabrication

Publication

EP 0914973 A3 20011010 (EN)

Application

EP 98308972 A 19981103

Priority

JP 30201897 A 19971104

Abstract (en)

[origin: EP0914973A2] A pneumatic tyre for passenger cars which is improved in harshness noise without deteriorating the steering stability is disclosed, wherein a harshness factor HF is set in the range of from 3.2 to 3.5, the harshness factor HF being: $\frac{Kv}{R1}$ where R1 is a radius of curvature (mm) of a crown part (Cr) of the tread profile, R2 is a radius of curvature (mm) of shoulder parts (Sh) of the tread profile, and Kv is the vertical spring constant (KN/mm) of the tyre. <IMAGE>

IPC 1-7

B60C 11/00; **B60C 3/04**

IPC 8 full level

B60C 3/00 (2006.01); **B60C 11/00** (2006.01); **B60C 11/01** (2006.01)

CPC (source: EP US)

B60C 3/00 (2013.01 - EP US); **B60C 11/00** (2013.01 - EP US); **B60C 11/0083** (2013.01 - EP US); **Y10T 152/10495** (2015.01 - EP US)

Citation (search report)

- [X] EP 0346106 A1 19891213 - SUMITOMO RUBBER IND [JP]
- [A] EP 0790142 A1 19970820 - SUMITOMO RUBBER IND [JP]
- [A] EP 0402303 A1 19901212 - GOODYEAR TIRE & RUBBER [US]
- [A] EP 0295898 A1 19881221 - SUMITOMO RUBBER IND [JP]
- [A] PATENT ABSTRACTS OF JAPAN vol. 018, no. 526 (M - 1683) 5 October 1994 (1994-10-05)

Cited by

EP1086832A3; WO0069660A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0914973 A2 19990512; **EP 0914973 A3 20011010**; **EP 0914973 B1 20080917**; DE 69840013 D1 20081030; JP 3425071 B2 20030707; JP H11129704 A 19990518; US 6167932 B1 20010102

DOCDB simple family (application)

EP 98308972 A 19981103; DE 69840013 T 19981103; JP 30201897 A 19971104; US 18574998 A 19981104