

Title (en)
Awning

Title (de)
Ausfallmarkise

Title (fr)
Store

Publication
EP 0916780 A3 20010704 (DE)

Application
EP 98121438 A 19981111

Priority
DE 19750985 A 19971118

Abstract (en)
[origin: DE19750985C1] The drop-out arm (16) is locked in the high adjusted position against outward pivoting. Its drop-out end (20) is connected to a sheet (24) and its other link end (18) is provided with a pivot link. The link end of the drop-out arm comes into contact with a stop (42) in a specific vertically outwardly moved position. It runs over the stop and is thereby downwardly pivotable through 9 degrees. The drop-out arm in its direction of movement is activated by the force of a spring (17). The drop-out end (20) of the arm is guided in the guide rail (12). In the guide rail above the stop a recess (38) is provided at the point at which the drop out end (20) comes to locate, when the drop-out arm comes into contact with the stop and the drop-out end can come out of the guide rail over the recess.

IPC 1-7
E04F 10/06; E06B 9/92

IPC 8 full level
E06B 9/92 (2006.01)

CPC (source: EP)
E06B 9/92 (2013.01)

Citation (search report)

- [XAY] FR 788667 A 19351014 - BAUMANN & FILS
- [Y] EP 0798442 A1 19971001 - MADO NEDERLAND [NL]
- [YA] CH 192788 A 19370915 - ROLLADENFABRIK A GRIESSER A G [CH]
- [Y] CH 193006 A 19370930 - SCHENKER EMIL [CH]

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
DE 19750985 C1 19990128; EP 0916780 A2 19990519; EP 0916780 A3 20010704

DOCDB simple family (application)
DE 19750985 A 19971118; EP 98121438 A 19981111