

Title (en)

A TIRE TREAD HAVING FLOW-THROUGH GROOVES

Title (de)

REIFENLAUFFLACHE MIT DURCHFLUSSNUTEN

Title (fr)

BANDE DE ROULEMENT DE PNEUMATIQUE DOTEE DE SILLONS POUR ECOULEMENT DIRECT

Publication

EP 0918654 A1 19990602 (EN)

Application

EP 96924684 A 19960722

Priority

US 9612121 W 19960722

Abstract (en)

[origin: WO9803357A1] Method of molding a tire tread and a tread (6) are disclosed. The mold (2) has at least one mold rib (20) having a plurality of notches cut into the rib forming flow paths (30) across the mold rib which allow the tread rubber to uniformly flow to adjacent tread element forming recesses (22) within the mold (2). The resultant tread (6) has at least one groove (40) having rubber filled flow paths (30).

IPC 1-7

B60C 11/12; **B60C 11/04**; **B29D 30/06**

IPC 8 full level

B60C 11/00 (2006.01); **B29C 33/02** (2006.01); **B29C 35/02** (2006.01); **B29D 30/06** (2006.01); **B60C 11/04** (2006.01); **B60C 11/11** (2006.01); **B60C 11/12** (2006.01); **B60C 11/13** (2006.01)

CPC (source: EP)

B29D 30/0606 (2013.01); **B60C 11/047** (2013.01); **B60C 11/13** (2013.01); **B60C 11/1369** (2013.01); **B29D 2030/0612** (2013.01); **B60C 2011/1361** (2013.01)

Citation (search report)

See references of WO 9803357A1

Cited by

US2016167444A1; US2023137725A1; EP4201702A1

Designated contracting state (EPC)

DE ES FR GB IT NL

DOCDB simple family (publication)

WO 9803357 A1 19980129; AR 007957 A1 19991124; AU 6507596 A 19980210; BR 9612681 A 19990720; CA 2261237 A1 19980129; DE 69616386 D1 20011129; DE 69616386 T2 20020704; EP 0918654 A1 19990602; EP 0918654 B1 20011024; JP 2000515081 A 20001114; TW 344703 B 19981111; ZA 976191 B 19980203

DOCDB simple family (application)

US 9612121 W 19960722; AR P970103289 A 19970722; AU 6507596 A 19960722; BR 9612681 A 19960722; CA 2261237 A 19960722; DE 69616386 T 19960722; EP 96924684 A 19960722; JP 50688298 A 19960722; TW 86110343 A 19970721; ZA 976191 A 19970711