

Title (en)

Method for adjusting the blasting image and impeller wheel suitable for carrying out the method

Title (de)

Verfahren zur Strahlbildnachstellung sowie zur Durchführung des Verfahrens geeignetes Schleuderrad

Title (fr)

Procédé d'ajustage de la projection d'abrasif et roue centrifuge adaptée pour la mise en oeuvre dudit procédé

Publication

**EP 0919334 B1 20030226 (DE)**

Application

**EP 98122333 A 19981125**

Priority

DE 19752549 A 19971127

Abstract (en)

[origin: DE19752549C1] The blast wheel has an external or internal sensor for detecting the wear and direction of wear of the aperture (2) to the particle steam guide tube (1). The sensor is connected to an electronic control circuit. The sensor output has an angular adjustment over the particle flow direction.

IPC 1-7

**B24C 5/06**

IPC 8 full level

**B24C 5/06** (2006.01)

CPC (source: EP)

**B24C 5/068** (2013.01)

Designated contracting state (EPC)

BE DE FR GB IT NL

DOCDB simple family (publication)

**DE 19752549 C1 19990408**; DE 59807299 D1 20030403; EP 0919334 A2 19990602; EP 0919334 A3 20001025; EP 0919334 B1 20030226

DOCDB simple family (application)

**DE 19752549 A 19971127**; DE 59807299 T 19981125; EP 98122333 A 19981125