

Publication

EP 0919507 A3 19990616

Application

EP 98119232 A 19981012

Priority

DE 29719565 U 19971104

Abstract (en)

[origin: EP0919507A2] The brake (1) ensures a brake force can be applied to the motor shaft (2) and/or a brake movement can be applied to a shaft coupled with the stepped belt. The brake moment of the operating brake can be varied at least during a time interval in the course of braking. The operating brake is preferably designed so that the brake moment is set to a predetermined starting value and then during operation of the brake increases as time progresses. The brake moment can be applied to the motor shaft by a main spring unit (13) whilst a secondary spring unit (17) is used to reduce the brake moment produced by the main spring unit. A damper (18) is connected in series with the secondary spring unit.

IPC 1-7

B66B 23/02

IPC 8 full level

B66B 23/02 (2006.01)

CPC (source: EP)

B66B 23/02 (2013.01)

Citation (search report)

- [XA] US 3830344 A 19740820 - CERVENEC S, et al
- [XA] US 5337878 A 19940816 - MEHLERT MARTIN [DE], et al
- [XA] US 4231452 A 19801104 - KRAFT JOSEPH K
- [A] PATENT ABSTRACTS OF JAPAN vol. 017, no. 527 (M - 1484) 22 September 1993 (1993-09-22)

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0919507 A2 19990602; EP 0919507 A3 19990616; EP 0919507 B1 20051116; AT E309954 T1 20051215; DE 29719565 U1 19980219;
DE 59813194 D1 20051222

DOCDB simple family (application)

EP 98119232 A 19981012; AT 98119232 T 19981012; DE 29719565 U 19971104; DE 59813194 T 19981012