

Title (en)
DEVICE FOR CONNECTING A DISPLACEABLE ELEMENT TO A GUIDE DEVICE

Title (de)
VORRICHTUNG ZUM VERBINDEN EINES VERSCHIEBBAREN ELEMENTES MIT EINER FÜHRUNGSVORRICHTUNG

Title (fr)
DISPOSITIF POUR RELIER UN ELEMENT DEPLA A BLE A UN DISPOSITIF DE GUIDAGE

Publication
EP 0920564 A1 19990609 (DE)

Application
EP 98925380 A 19980623

Priority
• CH 9800274 W 19980623
• CH 153397 A 19970624

Abstract (en)
[origin: WO9859140A1] The invention relates to a device (2) for connecting a displaceable element (1), especially a glass, metal or wooden panel to a guiding device (93; 93a), said guide device being guided in a rail (91; 91a). The inventive device comprises a first and a second fixing part (31; 41). Said fixing parts contain outer panels (32; 42) and fitting elements (33; 43) which can be interconnected by means of an axle (35). Said fitting elements (33; 43) are inserted into a cut out section (11) on the edge of the displaceable element (1) and interconnected. The fitting elements (33; 43) encompass a connection screw (6) which can be connected to the guide device (93; 93), said connection screw (6) having a screw shaft (63) with a screw head (62), a securing element (61) and a thread. The fitting element (33) of the first fixing part (31) has a channel (36) for receiving the screw shaft (63), said channel having channel walls (34), a trough (39) for receiving the screw head (62) and a cavity (37) for receiving the securing element (61). Said securing element (61) can be stopped by a stop screw (53; 53a). The fitting element (43) of the second fixing part (41) has a recess (44) for receiving the channel walls (34) and an opening through which the screw head (62) can be accessed. The assembled device is adjusted by loosening the stop screws (53) by a few turns and turning the connection screw (6) until the displaceable element (1) is set at the desired height. The stop screws (53) are then re-tightened. The securing element (61) is part of the connection screw (6) and is encompassed in the device (2) so that the top edge of the displaceable element (1) can be drawn practically up to the rail (91; 91a).

IPC 1-7
E05D 15/06

IPC 8 full level
E05D 15/06 (2006.01); **E05F 5/00** (2006.01)

CPC (source: EP KR US)
E05D 15/06 (2013.01 - KR); **E05D 15/063** (2013.01 - EP US); **E05F 5/003** (2013.01 - EP US); **E05Y 2201/218** (2013.01 - EP US); **E05Y 2201/22** (2013.01 - EP US); **E05Y 2201/48** (2013.01 - EP US); **E05Y 2201/638** (2013.01 - EP US); **E05Y 2201/64** (2013.01 - EP US); **E05Y 2201/688** (2013.01 - EP US); **E05Y 2201/702** (2013.01 - EP US); **E05Y 2600/20** (2013.01 - EP US); **E05Y 2800/672** (2013.01 - EP US); **E05Y 2900/00** (2013.01 - EP US)

Citation (search report)
See references of WO 9859140A1

Designated contracting state (EPC)
AT BE CH DE DK ES FI FR GB GR IE IT LI NL PT SE

DOCDB simple family (publication)
WO 9859140 A1 19981230; **WO 9859140 A9 20010201**; AT E227387 T1 20021115; AU 732336 B2 20010412; AU 7755498 A 19990104; CA 2263507 A1 19981230; CA 2263507 C 20070911; DE 59806174 D1 20021212; DK 0920564 T3 20030310; EP 0920564 A1 19990609; EP 0920564 B1 20021106; ES 2186167 T3 20030501; JP 2001503115 A 20010306; JP 3694034 B2 20050914; KR 100573463 B1 20060424; KR 20000068319 A 20001125; PT 920564 E 20030331; TW 357223 B 19990501; US 6052867 A 20000425

DOCDB simple family (application)
CH 9800274 W 19980623; AT 98925380 T 19980623; AU 7755498 A 19980623; CA 2263507 A 19980623; DE 59806174 T 19980623; DK 98925380 T 19980623; EP 98925380 A 19980623; ES 98925380 T 19980623; JP 50349399 A 19980623; KR 19997001480 A 19990224; PT 98925380 T 19980623; TW 87112350 A 19980728; US 14771399 A 19990325