

Title (en)

Method for connecting at least two metal sheets

Title (de)

Verfahren zum Fügen mindestens zweier Blechteile

Title (fr)

Méthode de connection d' au moins deux tôles

Publication

EP 0920934 A1 19990609 (DE)

Application

EP 98120974 A 19981105

Priority

DE 19748791 A 19971105

Abstract (en)

A nipple (12) is deep-drawn from one part (10) and upset, so that a bead (16) is formed on opposite sides of the nipple. A second part (30) is cut along two parallel lines, and the material between the lines is pressed out. The nipple bead of the first part is fitted into the area between the cutting lines (34) so that the bead engages behind the cut edges. The pressed-out material (32) of the second part remains connected by a web.

Abstract (de)

Zwei Blechteile werden vorzugsweise mit geringer Montagekraft (z.B. Handkraft) miteinander gefügt, indem ein am ersten Blechteil (10) tiefgezogener und gestauchter Nippel (12) in eine komplementäre Ausnehmung des andern Blechteils (30) infolge überwiegend elastischer Verformung des Nippels und der Ausnehmung eingeschnappt wird. <IMAGE>

IPC 1-7

B21D 39/03; F16B 5/04

IPC 8 full level

B21D 39/03 (2006.01)

CPC (source: EP)

B21D 39/03 (2013.01)

Citation (search report)

- [X] GB 160228 A 19210308 - FRANK ARNOLD DARRAH
- [A] EP 0434447 A1 19910626 - DU PONT [US]

Designated contracting state (EPC)

AT CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

DE 19748791 A1 19990506; **DE 19748791 C2 19990819**; EP 0920934 A1 19990609

DOCDB simple family (application)

DE 19748791 A 19971105; EP 98120974 A 19981105