

Title (en)
Elastic feeding trough

Title (de)
Elastische Speisemulde

Title (fr)
Auge élastique d'alimentation

Publication
EP 0926274 B2 20070530 (DE)

Application
EP 98811105 A 19981104

Priority
CH 295297 A 19971223

Abstract (en)
[origin: EP0926274A2] The feed trough (20) for fiber materials, at a textile machine, has a bend-resistant carrier (22) and at least one gap unit (24) attached to it which has elastic distortion. The gap unit has elastic distortion along the length of the roller against it, and has local elasticity. The gap unit is in one piece, along the roller length, and is in one piece with the carrier. The carrier is a hollow profile, with a holder (21) to act with a swing axis. The gap unit is curved, with a free-standing longitudinal edge (30), and a longitudinal edge secured to the carrier. The gap unit thickness decreases in the direction of fiber travel. The feed trough works with a sensor, such as a path movement or force sensor, to monitor the fiber mass between the trough and roller. The unit can have elasticity only in the edge zone of the free standing longitudinal edge, in a zone of 10-30 mm in the direction of fiber movement.

IPC 8 full level
D01G 15/20 (2006.01); **D01G 9/16** (2006.01)

CPC (source: EP)
D01G 9/16 (2013.01); **D01G 15/20** (2013.01)

Citation (opposition)
Opponent :

- DE 4200394 A1 19920924 - TRUETZSCHLER & CO [DE]
- EP 0275471 B1 19910424
- DE 4334035 A1 19940630 - TRUETZSCHLER GMBH & CO KG [DE]
- DE 724906 C 19420909 - SIEMENS AG

Cited by
WO2018189608A1; WO2018189607A1; CN108677284A; DE102011108615A1; CN103103635A; CH713691A1; CN110494601A; DE19855571A1; US6163931A; EP2077347A3; CH713692A1; CH713690A1; CN110462120A; CN110869549A; WO2018189595A1

Designated contracting state (EPC)
DE GB IT

DOCDB simple family (publication)
EP 0926274 A2 19990630; EP 0926274 A3 20000823; EP 0926274 B1 20040602; EP 0926274 B2 20070530; DE 59811509 D1 20040708

DOCDB simple family (application)
EP 98811105 A 19981104; DE 59811509 T 19981104