

Title (en)
Device for smoothing of shirts

Title (de)
Vorrichtung zum Glätten von Hemden

Title (fr)
Appareil pour le lissage de chemise

Publication
EP 0926293 B1 20020626 (DE)

Application
EP 98122801 A 19981201

Priority
DE 19754026 A 19971205

Abstract (en)
[origin: DE19754026A1] The device has a tensioner (14) for the button and buttonhole strips at the top and bottom ends of the button strip (7), at the carrier frame (1). The tensioners (14) can move against each other, and have support units (16,18) at an adjustable angle to the button strip (7). The spreading and tensioning support unit (15) is at the carrier frame (1) for the shirt waist and/or jibs with spreader supports for the cuffs (9) each with two spreaders with relative movements to each other. The supports are sleeve or half-sleeve cylinders. They are spread apart by a spring, and pressed together manually against the spring. The supports have perforated surfaces to allow a flow through them. The tensioner (14) has a number of clamping pads with counter surfaces. The pads have a grip surface structure, to hold the shirt (6) fabric, or both the pads and the counter surfaces have gripping claddings which are permeable to air and/or guide moisture passing through them. The shoulder supports (18) at the carrier frame (1) are at the level of the tensioner (14), at an angle to the button strip (7) line, which are adjustable to the shirt armhole seam (11) on linkage mountings. Individual radiant and/or convection heating units are at the supports. A machine drive sets the carrier frame and/or the shirt supports. A fan blower (4) is fitted to the carrier frame (1), with its pressure side towards the shirt (6) interior. The supports for the shirt waist (8), neck (12) and cuffs (9) are open, and have air guides, and an air guide (17) is between the blower (4) and the waist support (15), which can be adjusted for length and position. The carrier frame has a smooth surface at the button strip (7). A central control sets the position of the carrier frame (1) and the supports. The carrier frame (1) is on a vertical pillar (2), with a base fitted with rollers (3).

IPC 1-7
D06F 73/00

IPC 8 full level
D06F 71/20 (2006.01); **D06F 73/00** (2006.01)

CPC (source: EP)
D06F 71/20 (2013.01); **D06F 73/00** (2013.01)

Cited by
CN108004747A; EP1600550A1; ITMO20090011A1; EP3779026A1; CN112971513A; DE10156859A1; CN111297065A; WO2021180776A1; WO2010084396A3; WO2004057089A1; CN113874577A; EP3933099A4; US11751722B2; US11766152B2; US11832761B2

Designated contracting state (EPC)
DE ES FR GB IT SE

DOCDB simple family (publication)
DE 19754026 A1 19990610; DE 59804574 D1 20020801; EP 0926293 A1 19990630; EP 0926293 B1 20020626; ES 2179416 T3 20030116

DOCDB simple family (application)
DE 19754026 A 19971205; DE 59804574 T 19981201; EP 98122801 A 19981201; ES 98122801 T 19981201