

Title (en)

Arm for securing structures

Title (de)

Verankerungsarm für Strukturen

Title (fr)

Bras d'ancrage pour structures

Publication

EP 0931894 A1 19990728 (EN)

Application

EP 98500128 A 19980528

Priority

ES 9800188 U 19980126

Abstract (en)

Fitted at one end with a clamp (3) for securing the arm to the structure and at the other end with another clamp, plate or similar, for securing the arm to the facade, it has a telescopic structure using two tubular sections (1) and (2) giving the arm a variable length. Longitudinal adjustment of the arm is by means of a pin (5) which passes through a single orifice in one of the sections of tube (1) and one of the multiple orifices (7) in the other tube (2) so that the effective length of the arm will depend on the orifice selected (7). The two tubes (1) and (2) making up the arm are joined permanently to one other by means of an internal chain or cable (14) which allows telescopic displacement but makes detachment impossible. The pin (5) is mounted on a bridge (6) which, though allowing axial mobility also prevents detachment and possible loss. <IMAGE>

IPC 1-7

E04G 5/04

IPC 8 full level

E04G 5/04 (2006.01)

CPC (source: EP)

E04G 5/04 (2013.01)

Citation (search report)

- [XY] FR 1165329 A 19581021
- [Y] EP 0451068 A1 19911009 - PERRUELLE CLAUDE [FR]
- [A] DE 9417562 U1 19950216 - HAUSER JOHANN [DE]
- [A] DE 19545654 A1 19970213 - GUCKEL FRANK [DE], et al
- [A] DE 3218046 A1 19831117 - BAUMANN WOLFGANG
- [A] GB 2230292 A 19901017 - WILBREY ROYSTON GEORGE
- [A] WO 9114061 A1 19910919 - PLUS EIGHT LIMITED [GB]
- [A] EP 0071376 A1 19830209 - RAYLOR J W & CO ENG [GB]

Cited by

CN110056180A; CN102953543A; GB2365911A; JP2020007769A; GB2505735A; GB2505735B

Designated contracting state (EPC)

DE FR GB IT PT

DOCDB simple family (publication)

EP 0931894 A1 19990728; ES 1039293 U 19981201; ES 1039293 Y 19990516

DOCDB simple family (application)

EP 98500128 A 19980528; ES 9800188 U 19980126