

Title (en)

Method and device for combining two suspension layers

Title (de)

Verfahren und Vorrichtung zum Zusammenführen zweier Suspensionsschichten

Title (fr)

Procédé et dispositif pour réunir deux couches de suspension

Publication

EP 0936306 B1 20020703 (DE)

Application

EP 99101270 A 19990123

Priority

DE 19806402 A 19980217

Abstract (en)

[origin: EP0936306A1] A process to combine a fiber suspension layer (1) with a further fiber suspension layer (2), where they are both brought together by layer carriers (3,4) into a wedge-shaped gap (5) for water extraction. The sides of the suspension layers (1,2) are restrained by guide surfaces (6,7). The guide surfaces are in contact with the sides of the suspensions directly before they come together and when they are combined, with no guide surface movement, or only a very restricted movement play. The guide surface contours are parallel to the layer carriers (3,4). An Independent claim is included for an apparatus with a fixed displacement body (10) in front of the wedge gap (5), with the guide surfaces (6,7). One guide surface (6) is generally parallel to the outer periphery of the facing cylinder section, and the other guide surface (7) is generally parallel to the facing fourdrinier (8). At least two fiber suspensions are fed into the wedge gap (5) from a stock inlet (11) at the upstream end of the wedge gap (5), between the cylinder (9) and the displacement body (10).

IPC 1-7

D21F 1/66

IPC 8 full level

D21D 1/40 (2006.01); **D21F 1/66** (2006.01)

CPC (source: EP US)

D21D 1/40 (2013.01 - EP US); **D21F 1/66** (2013.01 - EP US)

Designated contracting state (EPC)

AT DE FR IT

DOCDB simple family (publication)

EP 0936306 A1 19990818; **EP 0936306 B1 20020703**; AT E220141 T1 20020715; DE 19806402 A1 19990819; DE 59901887 D1 20020808; US 6558557 B1 20030506

DOCDB simple family (application)

EP 99101270 A 19990123; AT 99101270 T 19990123; DE 19806402 A 19980217; DE 59901887 T 19990123; US 24979499 A 19990216