

Title (en)  
FUEL INJECTION VALVE

Title (de)  
KRAFTSTOFFEINSPRITZVENTIL

Title (fr)  
INJECTEUR DE CARBURANT

Publication  
**EP 0937203 B1 20020515 (DE)**

Application  
**EP 98916807 A 19980227**

Priority  
• DE 9800575 W 19980227  
• DE 19739905 A 19970911

Abstract (en)  
[origin: DE19739905A1] The invention relates to a fuel injection valve for internal combustion engines comprising a valve member (5) moving outwards from the valve body (1). At least two axially superimposed rows of injection holes (23) are provided for on said valve member, which holes can be controlled in sequence during the opening stroke directed towards the outside of the valve member (5). The valve further comprises a two-stage hydraulic valve lift stop which delimits the opening stroke path of the valve member (5) and is configured as a hydraulic damping chamber (39) with controllable relief. Relief is obtained by means of at least two ground faces (51, 59) on the valve member (5) which can be controlled in sequence during the opening stroke of the valve member (5). At least one of said ground faces can be connected to a low-pressure chamber via a relief channel (63) containing a valve (65).

IPC 1-7  
**F02M 61/08**

IPC 8 full level  
**F02M 45/08** (2006.01); **F02M 61/04** (2006.01); **F02M 61/08** (2006.01); **F02M 61/16** (2006.01); **F02M 61/20** (2006.01); **F02M 63/00** (2006.01)

CPC (source: EP US)  
**F02M 61/045** (2013.01 - EP US); **F02M 61/08** (2013.01 - EP US); **F02M 61/205** (2013.01 - EP US); **F02M 2200/304** (2013.01 - EP US)

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**DE 19739905 A1 19990318**; DE 59804130 D1 20020620; EP 0937203 A1 19990825; EP 0937203 B1 20020515; JP 2001504915 A 20010410; US 6105879 A 20000822; WO 9913214 A1 19990318

DOCDB simple family (application)  
**DE 19739905 A 19970911**; DE 59804130 T 19980227; DE 9800575 W 19980227; EP 98916807 A 19980227; JP 51488699 A 19980227; US 29782599 A 19990610