

Title (en)

FLAT CABLE AND METHOD OF MANUFACTURING THE SAME

Title (de)

FLACHKABEL UND SEIN HERSTELLUNGSVERFAHREN

Title (fr)

CABLE PLAT ET PROCEDE DE FABRICATION

Publication

**EP 0938099 A1 19990825 (EN)**

Application

**EP 98919609 A 19980515**

Priority

- JP 9802145 W 19980515
- JP 12738497 A 19970516

Abstract (en)

There are provided a flat cable having excellent life characteristics at the time of repeated flection and a method of manufacturing the flat cable with high productivity. In a flat cable in which a plurality of rectangular conductors arranged in parallel are buried in an insulating resin layer, the insulating resin layer in contact with at least the rectangular conductors is an extrusion coating layer formed of a thermoplastic resin with a flexural modulus of 800 to 2400 MPa. The flat cable is manufactured by feeding a plurality of rectangular conductors arranged in parallel to a cross-head of an extruder and by supplying the thermoplastic resin to extrusion coat the rectangular conductors. <IMAGE>

IPC 1-7

**H01B 7/08; H01B 13/00**

IPC 8 full level

**H01B 7/08** (2006.01); **H01B 13/14** (2006.01)

CPC (source: EP KR)

**H01B 7/08** (2013.01 - KR); **H01B 7/0823** (2013.01 - EP); **H01B 13/14** (2013.01 - EP); **H01B 13/144** (2013.01 - EP)

Citation (search report)

See references of WO 9852199A1

Cited by

DE102016114944A1; EP1453068A1; US2013000950A1; US9793030B2; EP1389784A1; DE10238188A1; EP2879248A4; US9263172B2; US6954983B2; US10147516B2; US7989701B2; WO2012154256A1; WO2013014903A1; WO2004019349A1

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

**EP 0938099 A1 19990825**; CN 1226993 A 19990825; JP 3700861 B2 20050928; KR 20000023728 A 20000425; WO 9852199 A1 19981119

DOCDB simple family (application)

**EP 98919609 A 19980515**; CN 98800642 A 19980515; JP 54905798 A 19980515; JP 9802145 W 19980515; KR 19997000189 A 19990112