

Title (en)
Process and apparatus for spinning, drawing and winding up of a yarn

Title (de)
Verfahren und Vorrichtung zum Spinnen, Verstrecken und Aufwickeln eines Fadens

Title (fr)
Procédé et dispositif pour le filage, l'étirage et le bobinage d'un fil

Publication
EP 0940485 A3 19991229 (DE)

Application
EP 99102844 A 19990301

Priority
DE 19809381 A 19980305

Abstract (en)
[origin: EP0940485A2] In the operation of spinning, drawing and winding a synthetic filament yarn, the spun filaments are eddied in an eddy jet within the drawing zone and before it leaves the drawing godet. The filament material passes a number of times round the drawing godet and a deflection roller, to be eddied at the final wound coil between the godet and the deflection roller. The filament material is heated by the godet mantle directly before it is eddied in the jet, where a hot air stream is aligned along or against the direction of travel. The filament material is also eddied before it enters the drawing zone. An Independent claim is included for a filament spinning assembly with an eddy jet (21) in front of the final drawing godet (19) in the drawing zone (2), in the direction of travel. Preferred Features: The final drawing godet has a deflection roller (20), forming a drawing godet unit (16), where the filament material (14) passes round them a number of times. The eddy jet is between the godet and deflection roller in the direction of travel, at the final coil winding before it leaves the godet. The mantle surface of the drawing godet has a roughness where the final coil winding lies which is less than at the remaining mantle surface. The godet mantle has a smaller diameter for the final filament coil winding than at the other godet mantle surface zones. The eddy jet has a filament channel to guide and eddy the filament material. An air channel opens into the filament channel, to form an included angle between the channels of ≤ 90 degrees in the direction of travel. The drawing godet has a heater to give a heated mantle. The drawing godet and deflection roller of the drawing godet unit have their own drives. An eddy jet can be in the filament path between the spinning station (1) and the drawing zone.

IPC 1-7
D01D 5/16

IPC 8 full level
D01D 5/16 (2006.01); **D02J 1/08** (2006.01); **D02J 1/22** (2006.01); **D02J 13/00** (2006.01)

CPC (source: EP KR US)
D01D 5/16 (2013.01 - EP KR US); **D02J 1/08** (2013.01 - EP KR US); **D02J 1/22** (2013.01 - EP KR US); **D02J 13/005** (2013.01 - EP KR US)

Citation (search report)

- [XY] LU 76926 A1 19770926
- [Y] EP 0703306 A1 19960327 - BALLARATI VITO [IT]
- [Y] DE 3125527 A1 19820422 - BADISCHE CORP [US]
- [Y] DE 1660176 A1 19710812 - ALLIED CHEM
- [A] EP 0621357 A1 19941026 - TORAY INDUSTRIES [JP]
- [A] US 5066439 A 19911119 - NISHIKAWA KINSAKU [JP], et al
- [A] DE 2435009 A1 19760205 - BAYER AG
- [A] DE 2741193 A1 19790322 - BAYER AG
- [A] PATENT ABSTRACTS OF JAPAN vol. 017, no. 176 (C - 1045) 6 April 1993 (1993-04-06)
- [A] PATENT ABSTRACTS OF JAPAN vol. 011, no. 139 (C - 420) 7 May 1987 (1987-05-07)

Cited by
CN102373525A; EP1253222A3; US7322811B2; WO2004015173A1; WO2021079180A1; WO2006058667A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 0940485 A2 19990908; EP 0940485 A3 19991229; EP 0940485 B1 20050202; CN 1229151 A 19990922; CN 1263903 C 20060712; DE 59911539 D1 20050310; KR 100601346 B1 20060713; KR 19990082716 A 19991125; TW 518376 B 20030121; US 6120715 A 20000919

DOCDB simple family (application)
EP 99102844 A 19990301; CN 99102074 A 19990305; DE 59911539 T 19990301; KR 19990007080 A 19990304; TW 88102198 A 19990211; US 26179799 A 19990303