

Title (en)  
Pneumatic screwdriver

Title (de)  
Pneumatischer Schrauber

Title (fr)  
Visseuse pneumatique

Publication  
**EP 0943401 B1 20011205 (FR)**

Application  
**EP 98401730 A 19980708**

Priority  
FR 9803370 A 19980319

Abstract (en)  
[origin: EP0943401A1] The pneumatic tool holder consists of, at one end, a connection for the air supply, and at the other end, a tool gripper. A pneumatic motor (2) is located within the holder with the valve to control the supply of air. A torque limiter is fitted between the motor and the tool and consists of a primary drive dog (48), fitted to the motor shaft, and a secondary drive dog (50), linked to the kinematic drive to the tool. Axial movement of the primary dog causes a reduction in air pressure to reduce the drive. The torque limiter consists of two drive dogs, with three drive teeth (53) are fitted on the face of the primary dog each with a hollow (54) towards the rear of the tooth. A drive ball (52) is fitted into each of the hollows.

IPC 1-7  
**B25B 23/145**

IPC 8 full level  
**B25B 23/145** (2006.01)

CPC (source: EP US)  
**B25B 23/145** (2013.01 - EP US)

Designated contracting state (EPC)  
DE ES GB IT SE

DOCDB simple family (publication)  
**EP 0943401 A1 19990922; EP 0943401 B1 20011205;** DE 69802778 D1 20020117; DE 69802778 T2 20020523; ES 2166131 T3 20020401;  
FR 2776220 A1 19990924; FR 2776220 B1 20000505; US 6085849 A 20000711

DOCDB simple family (application)  
**EP 98401730 A 19980708;** DE 69802778 T 19980708; ES 98401730 T 19980708; FR 9803370 A 19980319; US 11495098 A 19980827