

Title (en)

ATM adaption layer traffic scheduling

Title (de)

Verkehrsplanung in der ATM Anpassungsschicht

Title (fr)

Planification de trafic dans la couche d'adaptation ATM

Publication

**EP 0952752 B1 20130515 (EN)**

Application

**EP 99106050 A 19990325**

Priority

- CA 2233491 A 19980330
- US 20898298 A 19981211

Abstract (en)

[origin: EP0952752A2] ATM transmitting apparatus for transmitting messages, such as frame relay packets, associated with a plurality of connections comprises ATM layer transmission equipment for receiving multiple messages, segmenting each received message into a plurality of smaller data units, such as 48 byte AAL SAR protocol data units, and multiplexing such data units into a single stream for transport over a physical interface. A scheduler receives messages from each of the connections and transfers the messages to the transmission equipment. The scheduler dynamically sets a transmission rate for each connection, and allocates each connection whose message is transferred to the transmission equipment a substantially maximal amount of bandwidth at any given time during the transmission of the message, to thereby minimize interleaving of data units from the various connections and reduce the average latency (per unit of message) in transmitting the messages across a network.

<IMAGE> <IMAGE>

IPC 8 full level

**H04L 12/70** (2013.01); **H04L 12/56** (2006.01); **H04Q 11/04** (2006.01)

CPC (source: EP US)

**H04L 12/5602** (2013.01 - EP US); **H04Q 11/0478** (2013.01 - EP US); **H04L 2012/5653** (2013.01 - EP US); **H04L 2012/5679** (2013.01 - EP US)

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

**EP 0952752 A2 19991027**; **EP 0952752 A3 20001227**; **EP 0952752 B1 20130515**; US 2002150046 A1 20021017; US 7295558 B2 20071113

DOCDB simple family (application)

**EP 99106050 A 19990325**; US 12652702 A 20020422