

Publication

EP 0953699 A3 19991201

Application

EP 99105001 A 19990318

Priority

- DE 19815212 A 19980404
- DE 29806241 U 19980404
- DE 19831198 A 19980711

Abstract (en)

[origin: EP0953699A2] The two flat sides of the key shaft (2) have longitudinal grooves and or ridges which differ from the longitudinal profile of the tip part. The shaft at the key-bit has at least one key notch (5') in the key-bit in the tip part (4).for controlling a tumbler pin. The tip profile is thinner than the shaft profile so that it is contained inside the shaft profile.

IPC 1-7

E05B 19/00

IPC 8 full level

E05B 15/08 (2006.01); **E05B 19/00** (2006.01); **E05B 27/00** (2006.01)

CPC (source: EP)

E05B 15/08 (2013.01); **E05B 27/0042** (2013.01); **E05B 19/0052** (2013.01); **E05B 27/0007** (2013.01)

Citation (search report)

- [XA] WO 9106733 A1 19910516 - MEDECO SECURITY LOCKS [US]
- [A] EP 0634542 A1 19950118 - TRIOVING AS [NO]
- [A] US 4478061 A 19841023 - PREDDEY BRIAN F [AU]
- [A] DE 1553388 A1 19701210 - KESO AG
- [A] DE 2609777 A1 19761111 - GRUNDMANN ROHRBACHER SCHLOSSER, et al

Cited by

EP2031160A3; EP2360334A3; EP2990567A1; EP1806467A3; EP2031160A2; EP2770139A3

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0953699 A2 19991103; EP 0953699 A3 19991201; EP 0953699 B1 20010808; AT E204053 T1 20010815; DE 59900185 D1 20010913

DOCDB simple family (application)

EP 99105001 A 19990318; AT 99105001 T 19990318; DE 59900185 T 19990318