

Title (en)

Spark plug and process for fabricating the spark plug

Title (de)

Zündkerze und Herstellungsverfahren der Zündkerze

Title (fr)

Bougie d'allumage et méthode de fabrication de la bougie d'allumage

Publication

**EP 0954074 A2 19991103 (EN)**

Application

**EP 99303418 A 19990430**

Priority

JP 12144898 A 19980430

Abstract (en)

The invention provides a spark plug having an insulator which is composed mainly of alumina, and which is more superior in voltage endurance characteristics at high temperatures as compared with the prior-art materials. An insulator 2 of a spark plug 100 is made of an insulating material which is composed mainly of alumina, and which contains Al component within a range of 95 to 99.7 wt% in weight converted to Al<sub>2</sub>O<sub>3</sub>, and in which an area ratio occupied by alumina base principal-phase particles with particle size not less than 20 μm is not less than 50% as a cross-sectional structure of the insulator is observed. By making the alumina base principal-phase particles appropriately coarse like this, the voltage endurance characteristics of the insulator can be remarkably improved. <IMAGE>

IPC 1-7

**H01T 13/38; H01T 21/02**

IPC 8 full level

**C04B 35/111** (2006.01); **H01T 13/20** (2006.01); **H01T 13/38** (2006.01); **H01T 21/02** (2006.01)

CPC (source: EP US)

**H01T 13/38** (2013.01 - EP US); **H01T 21/02** (2013.01 - EP US)

Cited by

WO2008074438A1; CN102858713A; EP1104062A1; US6559579B2; WO2011133741A1; US6566793B2; US8614542B2

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

**EP 0954074 A2 19991103; EP 0954074 A3 20000202; EP 0954074 B1 20020102**; DE 69900732 D1 20020228; DE 69900732 T2 20020814; JP 3859354 B2 20061220; JP H11317279 A 19991116; US 6265816 B1 20010724

DOCDB simple family (application)

**EP 99303418 A 19990430**; DE 69900732 T 19990430; JP 12144898 A 19980430; US 30131999 A 19990429