

Title (en)
MECHANICAL AND THERMAL IMPROVEMENTS IN METAL HYDRIDE BATTERIES, BATTERY MODULES AND BATTERY PACKS

Title (de)
MECHANISCHE UND THERMISCHE VERBESSERUNG IN METALHYDRITBATTERIEN, BATTERIEMODULE UND -PAKETE

Title (fr)
AMELIORATIONS AU NIVEAU MECANIQUE ET THERMIQUE DANS LES BATTERIES, LES MODULES ET LES ENSEMBLES DE BATTERIES A HYDRURE METALLIQUE

Publication
EP 0956602 A4 20040922 (EN)

Application
EP 97902993 A 19970113

Priority
US 9700805 W 19970113

Abstract (en)
[origin: WO9831059A1] Mechanically and thermally improved rechargeable batteries, modules and fluid-cooled battery systems are disclosed herein. The battery is prismatic in shape with an optimized thickness to width to height aspect ratio which provides the battery with balanced optimal properties when compared to prismatic batteries lacking this optimized aspect ratio. The optimized thickness, width and height allow for maximum capacity and power output, while eliminating deleterious side effects. The battery case allows for unidirectional expansion which is readily compensated for by applying external mechanical compression counter to that direction. In the module (32), the batteries are bound within a bundling/compression means under external mechanical compression which is optimized to balance outward pressure due to expansion and provide additional inward compression to reduce the distance between the positive and negative electrodes, thereby increasing overall battery power. The fluid-cooled battery pack (39) includes a battery-pack case (40) having coolant inlets (41) and outlets (42); battery modules within the case such that they are spaced from the case walls and from each other to form coolant flow channels (43) along at least one surface of the bundled batteries; and at least one coolant transport means (44). The width of the coolant flow channels allows for maximum heat transfer. Finally, the batteries, modules and packs can also include means for providing variable thermal insulation to at least that portion of the rechargeable battery system which is most directly exposed to ambient thermal conditions, so as to maintain the temperature of the system within the desired operating range thereof under variable ambient conditions.

IPC 1-7
H01M 2/10; **H01M 10/50**; **H01M 10/52**

IPC 8 full level
H01M 10/34 (2006.01); **H01M 10/50** (2006.01); **H01M 50/103** (2021.01); **H01M 50/503** (2021.01); **H01M 10/04** (2006.01)

CPC (source: EP KR US)
H01M 10/0413 (2013.01 - EP KR); **H01M 10/0468** (2013.01 - EP KR); **H01M 10/345** (2013.01 - EP KR); **H01M 10/613** (2015.04 - EP KR); **H01M 10/635** (2015.04 - EP KR); **H01M 10/647** (2015.04 - EP KR); **H01M 10/652** (2015.04 - EP KR); **H01M 10/653** (2015.04 - EP KR); **H01M 10/6551** (2015.04 - EP KR); **H01M 10/6557** (2015.04 - EP KR); **H01M 10/6563** (2015.04 - EP KR); **H01M 10/658** (2015.04 - KR); **H01M 50/103** (2021.01 - EP KR US); **H01M 50/325** (2021.01 - EP KR); **H01M 50/503** (2021.01 - EP KR US); **H01M 10/658** (2015.04 - EP); **Y02E 60/10** (2013.01 - EP KR); **Y02P 70/50** (2015.11 - EP KR)

Citation (search report)

- [A] US 4468440 A 19840828 - EVJEN JOHN M [US]
- [A] US 3463672 A 19690826 - SCHMIDT JACOB E
- [A] EP 0533317 A2 19930324 - HONDA MOTOR CO LTD [JP]
- See references of WO 9831059A1

Designated contracting state (EPC)
DE ES FR GB IT

DOCDB simple family (publication)
WO 9831059 A1 19980716; AU 1703497 A 19980803; AU 737894 B2 20010906; CA 2276569 A1 19980716; CA 2276569 C 20061114; EP 0956602 A1 19991117; EP 0956602 A4 20040922; JP 2001507856 A 20010612; JP 4286909 B2 20090701; KR 100422175 B1 20040310; KR 100449983 B1 20040922; KR 20000070071 A 20001125; KR 20030066763 A 20030809; KR 20030066764 A 20030809; KR 20030066765 A 20030809; KR 20040031078 A 20040409; UA 46888 C2 20020617

DOCDB simple family (application)
US 9700805 W 19970113; AU 1703497 A 19970113; CA 2276569 A 19970113; EP 97902993 A 19970113; JP 53082398 A 19970113; KR 19997006292 A 19990712; KR 20037008622 A 20030625; KR 20037008623 A 20030625; KR 20037008624 A 20030625; KR 20047003613 A 19971113; UA 99084633 A 19970113