

Title (en)
Strip winding apparatus

Title (de)
Dünnbandwickelvorrichtung

Title (fr)
Dispositif d'enroulement d'une bande

Publication
EP 0958867 A3 20010502 (DE)

Application
EP 99109588 A 19990514

Priority
US 8212398 A 19980519

Abstract (en)
[origin: EP0958867A2] The flap guide (20) can selectively be moved into at least two positions. In a first position, the guide locates on at least one of the clamp rollers (10,12) so that it impedes it. The band (14) is thus forced to deviate from a normal path in order at an angle to follow a path to the winding pin (16) and a second position in which the guide does not locate on the clamp roller. This process prevents unnecessary wear or groove formation on the surface of the clamp rollers during winding after the band has been brought into engagement with the winding pin and wound around it.

IPC 1-7
B21C 47/34

IPC 8 full level
B21C 47/34 (2006.01)

CPC (source: EP US)
B21C 47/34 (2013.01 - EP US); **B65H 2301/448** (2013.01 - EP US)

Citation (search report)

- [E] DE 19835110 A1 20000210 - SCHLOEMANN SIEMAG AG [DE]
- [XA] US 1326989 A 19200106 - AUGUST SUNDH
- [A] US 3688541 A 19720905 - OHKUBO HIROYUKI, et al
- [A] GB 1480685 A 19770720 - HOESCH WERKE AG
- [A] PATENT ABSTRACTS OF JAPAN vol. 017, no. 490 (M - 1474) 6 September 1993 (1993-09-06)

Cited by
CN111891803A; CN114700390A; DE10162433A1; DE10162433B4; US8256256B2; US10413952B2

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 0958867 A2 19991124; EP 0958867 A3 20010502; EP 0958867 B1 20070627; AT E365593 T1 20070715; DE 59914389 D1 20070809; ES 2293703 T3 20080316; US 6039283 A 20000321

DOCDB simple family (application)
EP 99109588 A 19990514; AT 99109588 T 19990514; DE 59914389 T 19990514; ES 99109588 T 19990514; US 8212398 A 19980519