

Title (en)
SENSORS WITH SUBMINIATURE THROUGH HOLES, AND METHOD FOR FABRICATING SUCH SENSORS

Title (de)
SENSOREN MIT SUBMINIATURDURCHGANGSLÖCHERN UND VERFAHREN ZU DEREN HERSTELLUNG

Title (fr)
DETECTEURS POSSEDANT DES PER AGES MINUSCULES ET PROCEDE DE FABRICATION DE CES DETECTEURS

Publication
EP 0961932 A1 19991208 (EN)

Application
EP 97923556 A 19970506

Priority

- US 9707602 W 19970506
- US 64900996 A 19960516
- US 64867696 A 19960516
- US 64867596 A 19960516

Abstract (en)
[origin: WO9743634A1] The present invention is a sensor having an electrode formed in electrical contact with a subminiature through hole. Because of the small diameter of the through hole, the material that fills the through hole and the through hole itself have an essentially negligible effect on the sensor. A relatively large number of sensors can be formed on the surface of the substrate within a relatively small fluid flowcell. Thus, more information can be attained using less analyte. The sensors of the present invention are preferably disposed on an alumina substrate which is essentially impervious to aqueous electrolytes and blood over long periods of storage in potentially corrosive environments. Since the substrate on which the sensors are deposited, and the encapsulants which insulate the conductive elements of the sensor do not break down or become unstable when exposed over time to such corrosive environments, the isolation that is provided remains very high between each sensor and each other sensor, between each sensor and each conduction path, and between each conduction path and each other conduction path. The superior isolation provides for a high level of accuracy in the sensor of the present invention. Furthermore, the use of the through holes allows the conduction paths between the electrodes of the sensors and any external devices to be exclusively on the opposite side of the substrate from the sample. This physical isolation of the sample from the conduction paths between the sensor electrodes and external devices ensures very high electrical isolation between each of the sensors is maintained over an extended period of time during which reactive fluids (such as electrolytes and/or blood) are present in the flowcell.

IPC 1-7
G01N 27/403; **G01N 33/487**; **G01N 27/28**; **G01N 27/30**

IPC 8 full level
G01N 27/28 (2006.01); **G01N 27/403** (2006.01); **G01N 33/487** (2006.01); **G01N 33/49** (2006.01)

CPC (source: EP)
G01N 33/4925 (2013.01)

Citation (search report)
See references of WO 9743634A1

Designated contracting state (EPC)
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 9743634 A1 19971120; AU 2933097 A 19971205; EP 0961932 A1 19991208; JP 2000512743 A 20000926; JP 4446028 B2 20100407

DOCDB simple family (application)
US 9707602 W 19970506; AU 2933097 A 19970506; EP 97923556 A 19970506; JP 54091697 A 19970506