

Title (en)
Scraping device

Title (de)
Abstreifvorrichtung

Title (fr)
Dispositif racleur

Publication
EP 0964190 B1 20040825 (DE)

Application
EP 99110224 A 19990526

Priority
DE 29810274 U 19980609

Abstract (en)
[origin: EP0964190A2] The wiper ring (7) encloses a rod-shaped structural part (4) with which it is in contact with a wiper lip (23), the structural part being axially movable, penetrating the breakthrough (3). The fixture device (19) contains a number of fixture arms (33) distributed in the peripheral direction of the wiper ring and extending away axially in an installation direction (34). The fixture arms have at least one radially outwardly extending fixture projection (35) and are spring-elastically deformable, so that the wiper ring, by means of impression into the breakthrough (3) in the assembly direction can be fixed in the frame of a securing connection to the retainer (1).

IPC 1-7
F16J 15/32; F16J 15/56

IPC 8 full level
F16J 15/32 (2006.01); **F16J 15/3268** (2016.01); **F16J 15/56** (2006.01)

CPC (source: EP)
F16J 15/3268 (2013.01)

Cited by
DE102009014814A1; US9862110B2; WO2010108573A1

Designated contracting state (EPC)
AT DE FR GB IT SE

DOCDB simple family (publication)
EP 0964190 A2 19991215; **EP 0964190 A3 20000906**; **EP 0964190 B1 20040825**; AT E274664 T1 20040915; DE 29810274 U1 19980917; DE 59910322 D1 20040930

DOCDB simple family (application)
EP 99110224 A 19990526; AT 99110224 T 19990526; DE 29810274 U 19980609; DE 59910322 T 19990526