

Title (en)

Hydraulic drive for a press

Title (de)

Hydraulischer Antrieb für eine Presse

Title (fr)

Entraînement hydraulique pour une presse

Publication

**EP 0972631 B1 20030326 (DE)**

Application

**EP 99111751 A 19990618**

Priority

DE 19831624 A 19980715

Abstract (en)

[origin: EP0972631A1] Press operation can be switched from 'simulation' with high plunger speed and low number of strokes, to 'production' with low speed and higher number of strokes. For this purpose, the pressure accumulator drive for a cylinder-piston unit (2) has an associated hydraulic transformer unit (27). This consists of a first hydraulic unit (28), formed as angle-adjustable hydraulic motor (29), and a second hydraulic unit (36), formed as an adjustable hydraulic pump, which is mechanically connected to the first. During simulation operation, the hydraulic accumulator (8) of the pump unit serves as drive for the first hydraulic unit.

IPC 1-7

**B30B 1/32; B30B 15/16**

IPC 8 full level

**B30B 1/32** (2006.01); **B30B 15/16** (2006.01); **B30B 15/24** (2006.01)

CPC (source: EP US)

**B30B 15/161** (2013.01 - EP US); **B30B 15/163** (2013.01 - EP US); **B30B 15/24** (2013.01 - EP US)

Citation (examination)

JP H09123000 A 19970513 - KAWASAKI YUKO KK

Cited by

AT516316B1; AT515369B1; WO2011021986A1

Designated contracting state (EPC)

DE ES FR IT SE

DOCDB simple family (publication)

**EP 0972631 A1 20000119; EP 0972631 B1 20030326**; DE 19831624 A1 20000120; DE 59904695 D1 20030430; US 6370873 B1 20020416

DOCDB simple family (application)

**EP 99111751 A 19990618**; DE 19831624 A 19980715; DE 59904695 T 19990618; US 35191899 A 19990714