

Title (en)

Pistol with precocked percussion pin

Title (de)

Pistole mit vorgespanntem Schlagbolzen

Title (fr)

Pistolet comportant un percuteur préarmé

Publication

EP 0973005 B1 20031119 (DE)

Application

EP 99890171 A 19990528

Priority

AT 47998 U 19980714

Abstract (en)

[origin: EP0973005A2] A piston with a tensioned bolt action has the bolt held back by a retainer (20). The bolt spring (8) is tensioned either by pulling back the slide or by the recoil of the previous round. The trigger release pushes back the retainer with a sliding action, backed by a second spring. The front of the retainer slides over a fixed support (35) for the initial part of the slide action, followed by a tilt action caused by a sloping part (37) of the retainer. This allows the retainer to be depressed by the force of the bolt spring and release the bolt. The retainer is reset to hold the bolt after the recoil action.

IPC 1-7

F41A 19/31

IPC 8 full level

F41A 17/46 (2006.01); **F41A 19/16** (2006.01); **F41A 19/31** (2006.01)

CPC (source: EP US)

F41A 17/46 (2013.01 - EP US); **F41A 19/16** (2013.01 - EP US); **F41A 19/31** (2013.01 - EP US)

Cited by

DE102005031927B3; DE102005031929A1; DE102005031929B4; DE102005031928A1; DE102005031928B4; WO2013093571A3

Designated contracting state (EPC)

AT BE DE ES FR IT

DOCDB simple family (publication)

EP 0973005 A2 20000119; EP 0973005 A3 20010307; EP 0973005 B1 20031119; AT 3024 U1 19990825; AT E254753 T1 20031215;
DE 59907777 D1 20031224; US 6263606 B1 20010724

DOCDB simple family (application)

EP 99890171 A 19990528; AT 47998 U 19980714; AT 99890171 T 19990528; DE 59907777 T 19990528; US 34367099 A 19990630