

Title (en)

Electronic ballast with inrush current limitation

Title (de)

Elektronisches Vorschaltgerät mit Einschaltstrombegrenzung

Title (fr)

Ballast électronique avec limitation du courant d'appel

Publication

**EP 0973359 B1 20040825 (DE)**

Application

**EP 99111406 A 19990611**

Priority

DE 19830368 A 19980707

Abstract (en)

[origin: EP0973359A2] The inverter (2) has a converter network (T1/1, T1/2, C1, SW3, SW4), arranged between a DC voltage potential (U+) or reference potential (Uref), with two bridge branches, which in a stationary condition are put through alternatively on the reference potential. Also the switch network is formed by limiting the switched ON current by a limit resistance (R1) which lies in series with the storage capacitor (C2), with a further connection at reference potential. The connecting point of the storage capacitor is coupled with limit resistance with the two bridge branches of the converter network.

IPC 1-7

**H05B 41/285; H02H 9/00**

IPC 8 full level

**H02H 9/00** (2006.01); **H05B 41/285** (2006.01)

CPC (source: EP US)

**H05B 41/2856** (2013.01 - EP US); **Y10S 315/07** (2013.01 - EP US)

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

**EP 0973359 A2 20000119; EP 0973359 A3 20021113; EP 0973359 B1 20040825;** CA 2276913 A1 20000107; CA 2276913 C 20080902;  
DE 19830368 A1 20000203; DE 59910327 D1 20040930; US 6078144 A 20000620

DOCDB simple family (application)

**EP 99111406 A 19990611;** CA 2276913 A 19990706; DE 19830368 A 19980707; DE 59910327 T 19990611; US 34691399 A 19990702