

Title (en)
Discharge lamp lighting device

Title (de)
Anordnung zum Betreiben einer Entladungslampe

Title (fr)
Dispositif pour alimenter une lampe à décharge

Publication
EP 0973361 A2 20000119 (EN)

Application
EP 99113453 A 19990712

Priority
JP 19884998 A 19980714

Abstract (en)

A discharge lamp lighting device in which dim control can be performed for a discharge lamp continuously and stably in a wide range, and which is simple in circuit configuration and low in price. The discharge lamp lighting device comprises: an inverter (IV) for turning on/off switching elements (Q2, Q3) by an oscillation output signal of an IV control integrated circuit (IC2) to thereby invert a voltage of a DC power supply (E) into high-frequency electric power, a discharge lamp (LA) capable of being lighted by the high-frequency electric power from the inverter (IV), a feedback circuit (FB) having delay time T (unit: second) expressed by $1/f \leq T \leq 1/10,000$ when the frequency of the high-frequency electric power is f, the feedback circuit (FB) including a reference value setting means (R15) for setting a reference value, the feedback circuit outputting a voltage for controlling the IV control integrated circuit (IC2) to make the high-frequency electric power equal to the reference value. <IMAGE>

IPC 1-7
H05B 41/392; H05B 41/282

IPC 8 full level
H05B 41/24 (2006.01); **H05B 41/282** (2006.01); **H05B 41/392** (2006.01)

CPC (source: EP US)
H05B 41/2828 (2013.01 - EP US); **H05B 41/3925** (2013.01 - EP US); **Y10S 315/04** (2013.01 - EP US)

Cited by
EP1395096A3; KR20010098937A; EP2175698A4

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 0973361 A2 20000119; EP 0973361 A3 20011024; JP 2000030887 A 20000128; JP 3600976 B2 20041215; TW 454426 B 20010911;
US 6194841 B1 20010227

DOCDB simple family (application)
EP 99113453 A 19990712; JP 19884998 A 19980714; TW 88109508 A 19990608; US 33476899 A 19990616