

Title (en)
APPLICATION FILMS

Title (de)
ÜBERTRAGUNGSFOLIEN

Title (fr)
FILMS D'APPLICATION

Publication
EP 0973651 A1 20000126 (EN)

Application
EP 98913390 A 19980402

Priority
• JP 9069997 A 19970409
• US 9806639 W 19980402

Abstract (en)
[origin: WO9845128A1] An application film which can be advantageously used as an intermediate transfer member in the application of a marking member to an adherend particularly in its complex three-dimensional area and, at the same time, has a good balance between softness, rubber elasticity, and stiffness. The film is constructed so that a backing film, when tested at a tensile speed of 200 mm/min according to the procedure set forth in JIS K 7127, has a 10 % modulus load of 0.3 to 1.6 kgf/15 mm, a 10 % modulus stress of 0.1 to 0.8 kgf/mm<2>, a 100 % modulus stress of 0.7 to 2.5 kgf/mm<2>, and a rate of change of modulus stress of not less than 3.0.

IPC 1-7
B44C 1/17; C09J 7/02

IPC 8 full level
B44C 1/165 (2006.01); **B44C 1/17** (2006.01); **C09J 7/02** (2006.01); **C09J 133/00** (2006.01); **C09J 201/00** (2006.01)

CPC (source: EP KR)
B44C 1/17 (2013.01 - EP KR)

Citation (search report)
See references of WO 9845128A1

Cited by
US2011064900A1; US6673419B1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
WO 9845128 A1 19981015; DE 69802392 D1 20011213; DE 69802392 T2 20020814; EP 0973651 A1 20000126; EP 0973651 B1 20011107;
JP 3655424 B2 20050602; JP H10287849 A 19981027; KR 20010006100 A 20010126

DOCDB simple family (application)
US 9806639 W 19980402; DE 69802392 T 19980402; EP 98913390 A 19980402; JP 9069997 A 19970409; KR 19997009178 A 19991007