

Title (en)
CONTROL VALVE APPARATUS

Title (de)
STEUER VENTIL

Title (fr)
SOUPAPE DE REGULATION

Publication
EP 0978931 A4 20010620 (EN)

Application
EP 98904413 A 19980223

Priority
JP 9800720 W 19980223

Abstract (en)
[origin: WO9943072A1] An elastic body (51) is provided to absorb the energy of collision generated by the collision of a rotor positioning section (31) against a shaft positioning section (29) when the initial position of a shaft section (24) is to be determined by shifting the shaft section (24) toward a female thread section (26), so that the noise of collision generated when the rotor positioning section (31) hits the shaft positioning section (29) can be reduced. Furthermore, the force of collision the rotor positioning section (31) exerts on the shaft positioning section (29) is reduced to prevent the rotor positioning section (31) and the shaft positioning section (29) from being deformed.

IPC 1-7
H02K 37/24; H02K 37/14; H02K 7/06; F02M 25/07; F16K 31/04

IPC 8 full level
H02K 7/06 (2006.01)

CPC (source: EP US)
H02K 7/06 (2013.01 - EP US)

Citation (search report)

- [YA] US 5718259 A 19980217 - MIYAKE TOSHIHIKO [JP], et al
- [Y] DE 3502222 A1 19860724 - WLM FEINWERKTECHNIK GMBH [DE]
- [PA] US 5769390 A 19980623 - ANDO SHOSAKU [JP] & DE 19624901 A1 19970109 - NISSAN MOTOR [JP]
- [A] US 4742989 A 19880510 - AKAGI MOTONOBU [JP]
- [A] PATENT ABSTRACTS OF JAPAN vol. 1997, no. 3 31 March 1997 (1997-03-31)
- [A] PATENT ABSTRACTS OF JAPAN vol. 1998, no. 6 30 April 1998 (1998-04-30)
- See references of WO 9943072A1

Cited by
US11862393B2

Designated contracting state (EPC)
DE FR GB SE

DOCDB simple family (publication)
WO 9943072 A1 19990826; DE 69839840 D1 20080918; EP 0978931 A1 20000209; EP 0978931 A4 20010620; EP 0978931 B1 20080806; JP 3753253 B2 20060308; US 6224034 B1 20010501

DOCDB simple family (application)
JP 9800720 W 19980223; DE 69839840 T 19980223; EP 98904413 A 19980223; JP 51994199 A 19980223; US 40340199 A 19991213