

Title (en)

Method for preventing flow instabilities in a burner

Title (de)

Verfahren zur Verhinderung von Strömungsinstabilitäten in einem Brenner

Title (fr)

Procédé pour prévenir les instabilités d'écoulement dans un brûleur

Publication

EP 0987491 B1 20050720 (DE)

Application

EP 98810924 A 19980916

Priority

EP 98810924 A 19980916

Abstract (en)

[origin: EP0987491A1] Disturbance air (22) is injected into the combustion air flow (15) in order to prevent the formation of coherent flow instabilities of the combustion air flow after outlet in the combustion chamber (28). The burner (26) has no premixing stretches and is operated with liquid or gaseous fuel.

IPC 1-7

F23C 7/00; F23D 17/00; F23C 7/02

IPC 8 full level

F23R 3/18 (2006.01); **F23C 7/00** (2006.01); **F23C 7/02** (2006.01); **F23D 17/00** (2006.01)

CPC (source: EP US)

F23C 7/002 (2013.01 - EP US); **F23C 7/02** (2013.01 - EP US); **F23D 17/002** (2013.01 - EP US); **F23C 2900/07002** (2013.01 - EP US);
F23D 2206/10 (2013.01 - EP US); **F23D 2210/00** (2013.01 - EP US)

Citation (examination)

EP 0851172 A2 19980701 - ABB RESEARCH LTD [CH]

Cited by

US6698209B1; DE10000415A1; EP1114967A1; US6834504B2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0987491 A1 20000322; EP 0987491 B1 20050720; DE 59812944 D1 20050825; JP 2000104923 A 20000411; US 6390805 B1 20020521

DOCDB simple family (application)

EP 98810924 A 19980916; DE 59812944 T 19980916; JP 25454099 A 19990908; US 38262899 A 19990825