

Title (en)
DISCHARGE LAMP WITH DIELECTRICALLY IMPEDED ELECTRODES

Title (de)
ENTLADUNGSLAMPE MIT DIELEKTRISCH BEHINDERTEN ELEKTRODEN

Title (fr)
LAMPE A DECHARGE A ELECTRODES PROTEGEES PAR UN DIELECTRIQUE

Publication
EP 0990262 A1 20000405 (DE)

Application
EP 99911602 A 19990218

Priority
• DE 9900450 W 19990218
• DE 19817475 A 19980420

Abstract (en)
[origin: US6310442B1] A discharge lamp (1) including a tubular discharge vessel (2), filled with inert gas and, optionally, a fluorescent layer, having at least three elongated electrodes (3, 4, 5) arranged parallel to the longitudinal axis of the tubular discharge vessel (2). The electrodes are arranged in such a manner that the relationship is satisfied, wherein s is the maximum spacing between an imaginary connecting line of an electrode pair and the most closely neighboring point on the wall of the tubular discharge vessel, and a is the mutual spacing between the electrodes of such electrode pair. A higher luminous density is achieved in this way. The lamp is particularly advantageous for a pulsed, dielectrically impeded discharge.

IPC 1-7
H01J 65/04; **H01J 65/00**

IPC 8 full level
H01J 65/00 (2006.01); **H01J 65/04** (2006.01)

CPC (source: EP KR US)
H01J 65/00 (2013.01 - EP US); **H01J 65/04** (2013.01 - KR); **H01J 65/046** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE DE FR GB IT NL

DOCDB simple family (publication)
US 6310442 B1 20011030; AT E264547 T1 20040415; CA 2294850 A1 19991028; CA 2294850 C 20070925; DE 19817475 A1 19991028; DE 19817475 B4 20040415; DE 59909153 D1 20040519; EP 0990262 A1 20000405; EP 0990262 B1 20040414; HU 224080 B1 20050530; HU P0002504 A2 20001128; HU P0002504 A3 20011228; JP 2002505801 A 20020219; KR 100602395 B1 20060720; KR 20010014032 A 20010226; TW 434641 B 20010516; WO 9954917 A1 19991028

DOCDB simple family (application)
US 44569699 A 19991213; AT 99911602 T 19990218; CA 2294850 A 19990218; DE 19817475 A 19980420; DE 59909153 T 19990218; DE 9900450 W 19990218; EP 99911602 A 19990218; HU P0002504 A 19990218; JP 55228199 A 19990218; KR 19997012061 A 19990218; TW 88104168 A 19990317