

Title (en)

Method and apparatus for a fiber optic jacket stripper

Title (de)

Verfahren und Vorrichtung zum Abmanteln von optischen Fasern

Title (fr)

Procédé et dispositif pour enlever la gaine d'une fibre optique

Publication

EP 0990929 A3 20040121 (EN)

Application

EP 99115027 A 19990803

Priority

US 12773798 A 19980803

Abstract (en)

[origin: EP0990929A2] A method and apparatus for stripping an outer jacket from a fiber optic cable is disclosed. The end of a fiber optic cable (390) is inserted between an upper cutting surface (310) and a lower cutting surface (320) in the fiber optic stripping tool. The fiber optic cable is engaged by the upper cutting surface substantially along a first half of the circumference of the outer jacket and the lower cutting surface substantially along the second half of the circumference of the outer jacket. The cutting surfaces cut through the circumference of the outer jacket. The cutting surfaces are disengaged from the jacket and the cut portion of the jacket is removed from the fiber optic cable. <IMAGE>

IPC 1-7

G02B 6/245; **G02B 6/44**

IPC 8 full level

H02G 1/12 (2006.01); **G02B 6/00** (2006.01); **G02B 6/245** (2006.01)

CPC (source: EP)

G02B 6/245 (2013.01)

Citation (search report)

- [X] US 4805301 A 19890221 - CHAPIN DAVID S [US], et al
- [X] US 4850108 A 19890725 - PERRINO JOSEPH A [US], et al
- [XA] GB 2204454 A 19881109 - BICC PLC
- [X] US 5003846 A 19910402 - YAGAWA HIROSHI [JP]
- [X] EP 0154375 A1 19850911 - PHILIPS PATENTVERWALTUNG [DE], et al

Cited by

KR100495397B1; CN100401605C; KR20020061688A; US2022120990A1; US11493722B2; US11982858B2; US8393250B2; US9748747B2

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0990929 A2 20000405; **EP 0990929 A3 20040121**; JP 2000056139 A 20000225

DOCDB simple family (application)

EP 99115027 A 19990803; JP 21961499 A 19990803