

Title (en)

Dispositif d'élimination du fil de sous-rendrage des broches sur un métier continu à filer ou à retordre

Title (de)

Vorrichtung zum Beseitigen von Unterwindungen an Spindeln einer Spinn- oder Zwirnmaschine

Title (fr)

Device for removing underwound yarn wraps from spindles of spinning or twisting machines

Publication

**EP 0994204 A1 20000419 (EN)**

Application

**EP 99402471 A 19991008**

Priority

FR 9812742 A 19981012

Abstract (en)

The mechanism (15) moves radially relative to the spindle, carried directly on a carriage (24). This has a slide (26) of which the front face (27) comes into contact with the spindle. This face defines the relative radial location between spindle and mechanism. Preferred features: The slide is spring- (25) loaded against the spindle. The flange raises the slide towards the spindle. The flange resists sliding wear. It contacts the spindle, not by its front face (27), but by two rollers. A suction nozzle carried near the knife, is connected to an extraction system able to remove the underwound thread immediately following cutting. The mechanism is cleared of thread pneumatically, including any pieces of it. A blower jet assists removal from the spindle, directing thread into a suction opening. The mechanism includes teeth forming a claw, and a tool with rough, sharp or abrasive projections. Teeth are distributed in rows and columns, running radially and axially with respect to the spindle. The equipment is further detailed.

Abstract (fr)

Dispositif pour l'élimination du fil de sous-rendrage des broches 2 sur un métier continu à filer ou à retordre 1, ce métier comportant une multiplicité de broches alignées sur au moins une face du métier, ce dispositif comportant un couteau 9 porté par un support 14 et agencé pour couper le fil de sous-rendrage de chaque broche entre la bobine en cours de formation portée par cette broche et les spires de sous-rendrage formées sur la broche, au-dessous de la bobine, caractérisé en ce qu'il comporte au surplus des moyens mécaniques 15 portés par le support à un niveau en hauteur situé au-dessous de celui du couteau 9 et agencés pour venir en contact direct avec les spires de sous-rendrage, après la coupe du fil de sous-rendrage par le couteau et alors que la broche tourne pour la formation de la bobine en cours, pour déchiqueter ou au moins arracher ou détruire le fil des spires de sous-rendrage. <IMAGE>

IPC 1-7

**D01H 1/38**

IPC 8 full level

**D01H 1/38** (2006.01)

CPC (source: EP)

**D01H 1/385** (2013.01)

Citation (search report)

- [A] EP 0730053 A2 19960904 - CHEMNITZER SPINNREIMASCHINEN [DE]
- [A] EP 0694634 A2 19960131 - MARZOLI & C SPA [IT]
- [A] DE 4432502 A1 19960314 - SCHURR STAHLCKER & GRILL [DE]

Cited by

CN110468475A; CN106854783A; CN103231943A; FR2815973A1; ES2193813A1; GR20010100348A

Designated contracting state (EPC)

BE DE FR IT

DOCDB simple family (publication)

**EP 0994204 A1 20000419**; FR 2784397 A1 20000414; FR 2784397 B1 20001222

DOCDB simple family (application)

**EP 99402471 A 19991008**; FR 9812742 A 19981012