

Title (en)  
Rock anchor and borehole with said anchor installed

Title (de)  
Anker sowie Bohrloch mit gesetztem Anker

Title (fr)  
Boulon d'ancrage et puits de forage avec ledit boulon posé

Publication  
**EP 0995878 A2 20000426 (DE)**

Application  
**EP 99890325 A 19991018**

Priority  
AT 175798 A 19981020

Abstract (en)  
A brace, with a tension element (3) carrying a molded end part (9) joined fluid-tightly to an outer sleeve (10), is new. A brace has a tension element (3) with several individual tension elements (especially of steel), an injection pipe (15) for injecting hardenable material (e.g. a cement mortar or a reactive plastic mixture) into a drilled hole, an outer sleeve (10) which encloses the tension element and which has a slip-resistant outer surface (especially an undulating surface, e.g. a thread) and optionally a bolt head. The hole base end of the tension element (3) carries a molded end part (9) which abuts the outer sleeve (10) and which is fluid-tightly joined to the sleeve (10), especially by a rubber-elastic casing (11, 13). An Independent claim is also included for a drilled hole in which the above brace is inserted.

Abstract (de)  
Anker, insbesondere Gebirgsanker, mit einem Zugglied (3), das mit einer Mehrzahl einzelner Einzelzugglieder (5), insbesondere aus Stahl, aufgebaut ist, einer Injektionsleitung (15), zumindest zum Bohrlochgrund, für erhärtendes Material, z. B. Zementmörtel, reaktive Kunststoffmischung, einer das Zugglied (3) umgebenden äußeren Umhüllung (10), mit einer Außenfläche, die einen erhöhten Widerstand gegen Verschiebung in Längsrichtung des Zuggliedes, insbesondere einen wellen- oder mäanderförmigen Längsschnitt, z. B. von einem auf der äußeren Umhüllung geformten Rundgewinde, aufweist und gegebenenfalls einem am Gebirge od. dgl. im oberen Kopfbereich des Ankers vorgesehenen Ankerkopf, und wobei am bohrlochgrundseitigen Ende der äußeren Umhüllung (10) das Zugglied (3) an dieser angreifbar ist, und wobei das Zugglied (3) am bohrlochgrundseitigen Ende einen angeformten Endteil (9) trägt, der an der äußeren Umhüllung (10), insbesondere am Stirnende derselben, abstützbar ist und daß der Endteil (9) mit der äußeren Umhüllung (10), insbesondere über ein gummielastisches Hüllstück (11, 13), fluiddicht verbunden ist. Zur Veröffentlichung gemeinsam mit der Zusammenfassung ist Fig. 1 bestimmt. <IMAGE>

IPC 1-7  
**E21D 21/00**

IPC 8 full level  
**E21D 21/00** (2006.01)

CPC (source: EP)  
**E21D 21/0033** (2013.01)

Citation (applicant)  
• EP 0393013 B1 19930505  
• DE 3335039 C1 19841031 - KLOECKNER BECORIT GMBH  
• DE 3507732 A1 19860918 - DYCKERHOFF & WIDMANN AG [DE]

Cited by  
EP1762699A1; CN111379566A; US7445406B2; WO03071098A1

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**EP 0995878 A2 20000426; EP 0995878 A3 20031029; AT 408473 B 20011227; AT A175798 A 20010415**

DOCDB simple family (application)  
**EP 99890325 A 19991018; AT 175798 A 19981020**