

Title (en)

Method for applying spacers of thermoplastic material to insulating glazing units

Title (de)

Verfahren zum Auftragen von Abstandhaltern für Isolierglasscheiben aus thermoplastischem Werkstoff

Title (fr)

Procédé d'application de cadres d'espacement en matériau thermoplastique aux vitrages isolants

Publication

**EP 0999331 A3 20010816 (DE)**

Application

**EP 99890355 A 19991105**

Priority

AT 184698 A 19981106

Abstract (en)

[origin: EP0999331A2] Temperature of the thermoplastic is measured at the coating point. Coating speed of the plastic along the edge is increased when this temperature rises above a set limit, and vice-versa. Preferred features: Coating pressure is held sensibly constant, over a given range of temperature departure from the desired value. Should the temperature become too low, pressure is increased and vice-versa. Temperature is also measured at a point spaced away from the coating point.

IPC 1-7

**E06B 3/673**; **B05C 5/02**

IPC 8 full level

**B05C 11/10** (2006.01); **E06B 3/673** (2006.01)

CPC (source: EP US)

**E06B 3/6733** (2013.01 - EP US); **B05C 11/1007** (2013.01 - EP US)

Citation (search report)

[A] US 5136974 A 19920811 - LISEC PETER [AT]

Cited by

CN103946471A

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 0999331 A2 20000510**; **EP 0999331 A3 20010816**; AT 406788 B 20000925; AT A184698 A 20000115; US 6491966 B1 20021210

DOCDB simple family (application)

**EP 99890355 A 19991105**; AT 184698 A 19981106; US 43411599 A 19991105