

Title (en)

Process for avoiding paint dropping on articles

Title (de)

Verfahren zur Vermeidung von Lacktropfen an Werkstücken

Title (fr)

Procédé pour éviter la formation de gouttes de peinture sur des objets

Publication

**EP 1000671 A3 20030212 (DE)**

Application

**EP 99121210 A 19991023**

Priority

DE 19851467 A 19981109

Abstract (en)

[origin: EP1000671A2] The paint droplet prevention method uses a collection element (3) lying on the outside of the employed surface of the paint sprayed workpiece (1b), for reception of any paint droplets (2b) via a gravitational and/or an electrical force. An Independent claim for a paint sprayed workpiece is also included.

IPC 1-7

**B05D 5/00**

IPC 8 full level

**B05D 5/00** (2006.01)

CPC (source: EP)

**B05D 5/00** (2013.01)

Citation (search report)

- [A] US 2359476 A 19441003 - GRAVLEY CHARLES K
- [A] US 3341353 A 19670912 - JOHNSON JOHN R
- [A] US 2950990 A 19600830 - JOHNSON DONALD D

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 1000671 A2 20000517; EP 1000671 A3 20030212; EP 1000671 B1 20040818;** AT E273758 T1 20040915; DE 19851467 A1 20000511; DE 59910264 D1 20040923

DOCDB simple family (application)

**EP 99121210 A 19991023;** AT 99121210 T 19991023; DE 19851467 A 19981109; DE 59910264 T 19991023